

INTRIGUE X ADVANCED E+ ELITE 3



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
SENSOR	RideControl Ergo 3, RideControl GO integrated in T/T
DISPLAY	ANT+ Wireless display compatible
BATTERY	EnergyPak Smart 400EnergyPak Plus range extender compatible
FRAME	
SIZES	XS, S, M, L
COLORS	Mirage/Cordovan
FRAME	Advanced-grade composite frame, AluXX SL-grade rear triangle, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender CompatibleMX (front 29", rear 27.5")
FORK	RockShox 35 Gold RL DebonAir, 150mm travel, 44mm offset, MotionControl™ rebound and lockout control, 15x110 Boost, Maxle Stealth, e-MTB optimized
SHOCK	Rock Shox Deluxe Select R, DebonAir, 185x52.5mm Trunnion mount, custom tuned
COMPONENTS	
HANDLEBAR	Giant Contact 35 Trail, 35x 760mm (XS-S), 780mm (M-L)
GRIPS	Liv Tactal Pro-E Single Lock-On Grips
STEM	Giant Contact SL 35
SEATPOST	Giant Contact Switch, dropper, 30,9mm (XS-S: 100/ M:125/ L:150)
SADDLE	Liv Sylvia E+
PEDALS	n/a
DRIVETRAIN	
SHIFTERS	Shimano Deore
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	Shimano Deore, 12-speed
BRAKES	Shimano BR-M420, 4-piston, hydraulic disc, 203mm
BRAKE LEVERS	Shimano Deore, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CHAIN	KMC e.12 Turbo, EcoProteq, e-bike optimized
CRANKSET	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (XS:160, S/M: 165, L:170)
BOTTOM BRACKET	n/a

WHEELS	
RIMS	AM30, Tubeless ready, 30mm inner width, 29" [F] / 27.5" [R]
HUBS	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPOKES	Sapim E-Lite [R] Race [F], e-bike optimized
TIRES	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)

Price: ₹ 5,999.00

GEOMETRY

FRAME	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	425	450
Seat Tube Angle	77.2° 78.0°	76.0° 76.7°	76.0° 76.7°
Top Tube Length (mm)	572 570	597 595	622 620
Head Tube Length (mm)	95	100	115
Head Tube Angle	65.7° 66.5°	65.8° 66.5°	65.8° 66.5°
Fork Rake (mm)	44	44	44
Trail (mm)	113 108	113 108	113 108
Wheelbase (mm)	1188 1190	1200 1201	1228 1229
Chain Stay Length (mm)	447 447	447 447	447 447
Bottom Bracket Drop (mm)	30 20	30 20	30 20
Stack (mm)	606 601	611 605	625 619
Reach (mm)	434 442	444 452	466 473
Stand Over Height (mm)	726 735	717 726	711 723
Handlebar Width (mm)	760	800	800
Stem Length (mm)	40	40	50
Crank Length (mm)	160	165	165
Wheel Size	R27.5" / F	R27.5" / F	R27.5" / F

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.