

INTRIGUE X ADVANCED E+ ELITE 3



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
SENSOR	RideControl Ergo 3, RideControl GO integrated in T/T
DISPLAY	ANT+ Wireless display compatible
BATTERY	EnergyPak Smart 400EnergyPak Plus range extender compatible
CADRU	
MARIMI	XS, S, M, L
CULORI	Mirage/Cordovan
CADRU	Advanced-grade composite frame, AluXX SL-grade rear triangle, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender CompatibleMX (front 29", rear 27.5")
FURCA	RockShox 35 Gold RL DebonAir, 150mm travel, 44mm offset, MotionControl™ rebound and lockout control, 15x110 Boost, Maxle Stealth, e-MTB optimized
SOC	Rock Shox Deluxe Select R, DebonAir, 185x52.5mm Trunnion mount, custom tuned
COMPONENTE	
GHIDON	Giant Contact 35 Trail, 35x 760mm (XS-S), 780mm (M-L)
GRIPS	Liv Tactal Pro-E Single Lock-On Grips
PIPA	Giant Contact SL 35
TIJA SA	Giant Contact Switch, dropper, 30,9mm (XS-S: 100/ M:125/ L:150)
SA	Liv Sylvia E+
PEDALE	n/a
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano Deore
SCHIMBATOR FATA	MRP HD2 co-moulded chain guide
SCHIMBATOR SPATE	Shimano Deore, 12-speed
FRANE	Shimano BR-M420, 4-piston, hydraulic disc, 203mm
MANETE FRANA	Shimano Deore, I-spec EV
PINIOANE	Shimano CS-M6100-12, 10-51T, 12-speed
LANT	KMC e.12 Turbo, EcoProteq, e-bike optimized
ANGRENAJ	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (XS:160, S/M: 165, L:170)
BOTTOM BRACKET	n/a

ROTI	
JANTE	AM30, Tubeless ready, 30mm inner width, 29" [F] / 27.5" [R]
BUTUCI	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPITE	Sapim E-Lite [R] Race [F], e-bike optimized
ANVELOPE	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)

GEOMETRIE

CADRU	XS	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	380	400	425	450
Seat Tube Angle	77,2° 78,0°	77,2° 78,0°	76,0° 76,7°	76,0° 76,7°
Top Tube Length (mm)	557 555	572 570	597 595	622 620
Head Tube Length (mm)	95	95	100	115
Head Tube Angle	65,7° 66,5°	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	113 108	113 108	113 108	113 108
Wheelbase (mm)	1174 1175	1188 1190	1200 1201	1228 1229
Chain Stay Length (mm)	447 447	447 447	447 447	447 447
Bottom Bracket Drop (mm)	30 20	30 20	30 20	30 20
Stack (mm)	606 601	606 601	611 605	625 619
Reach (mm)	419 427	434 442	444 452	466 473
Stand Over Height (mm)	722 730	726 735	717 726	711 723
Handlebar Width (mm)	760	760	800	800
Stem Length (mm)	40	40	40	50
Crank Length (mm)	160	160	165	165
Wheel Size	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F

Toate specificatiile enumerate se pot schimba fara notificare prealabila.