

INTRIGUE X ADVANCED E+ ELITE 3



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	SyncDrive Pro2 85Nm, powered by Yamaha
TIPALO	RideControl Ergo 3, RideControl GO integrated in T/T
PRIKAZOVALNIK	ANT+ Wireless display compatible
BATERIJA	EnergyPak Smart 400EnergyPak Plus range extender compatible
OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Mirage/Cordovan
OKVIR	Advanced-grade composite frame, AluXX SL-grade rear triangle, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender CompatibleMX (front 29", rear 27.5")
VILICE	RockShox 35 Gold RL DebonAir, 150mm travel, 44mm offset, MotionControl rebound and lockout control, 15x110 Boost, Maxle Stealth, e-MTB optimized
AMORTIZER	Rock Shox Deluxe Select R, DebonAir, 185x52.5mm Trunion mount, custom tuned
KOMPONENTE	
KRMILO	Giant Contact 35 Trail, 35x 760mm (XS-S), 780mm (M-L)
GRIPS	Liv Tactal Pro-E Single Lock-On Grips
OPORA KRMILA	Giant Contact SL 35
OPORA SEDEŽA	Giant Contact Switch, dropper, 30,9mm (XS-S: 100/ M:125/ L:150)
SEDEŽ	Liv Sylvia E+
PEDALA	n/a
POGON	
PRESTAVNE ROČICE	Shimano Deore
PREDNJI MENJALNIK	MRP HD2 co-moulded chain guide
ZADNJI MENJALNIK	Shimano Deore, 12-speed
ZAVORE	Shimano BR-M420, 4-piston, hydraulic disc, 203mm
ZAVORNE ROČICE	Shimano Deore, I-spec EV
VERIŽNIK	Shimano CS-M6100-12, 10-51T, 12-speed
VERIGA	KMC e.12 Turbo, EcoProteq, e-bike optimized
GONILKE Z VERIŽNIKI	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (XS:160, S/M: 165, L:170)
BOTTOM BRACKET	n/a

OBROČNIKI	
OBROČI	AM30, Tubeless ready, 30mm inner width, 29" [F] / 27.5" [R]
PESTA	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
NAPERE	Sapim E-Lite [R] Race [F], e-bike optimized
PLAŠČI	Maxxis Minion DHF 29x2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
DODATKI	Tubeless kit (liquid, valves, levers, manual, tool)

GEOMETRIJA

OKVIR	XS		S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	380	400	425	450				
Kot sedežne cevi	77,2°	78,0°	77,2°	78,0°	76,0°	76,7°	76,0°	76,7°
Top Tube Length (mm)	557	555	572	570	597	595	622	620
Višina glave okvirja (mm)	95	95	100	115				
Krmilni kot	65,7°	66,5°	65,7°	66,5°	65,8°	66,5°	65,8°	66,5°
Zamik vpetja osi (mm)	44	44	44	44				
Trail (mm)	113	108	113	108	113	108	113	108
Medosna razdalja (mm)	1174	1175	1188	1190	1200	1201	1228	1229
Dolžina cevi ob verigi (mm)	447	447	447	447	447	447	447	447
Bottom Bracket Drop (mm)	30	20	30	20	30	20	30	20
Oddaljenost zgornje cevi od gonilne osi (mm)	606	601	606	601	611	605	625	619
Doseg (mm)	419	427	434	442	444	452	466	473
Višina zgornje cevi (mm)	722	730	726	735	717	726	711	723
Širina krmila (mm)	760	760	800	800				
Dolžina opore krmila (mm)	40	40	40	50				
Dolžina gonilke (mm)	160	160	165	165				
Velikost obročnikov	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F				

Vse navedene specifikacije se lahko spremenijo brez obvestila.