



## ŠPECIFIKÁCIE

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 80Nm, Powered by YAMAHA
OVLÁDAČ	RideControl Ergo
OVLÁDACIA JEDNOTKA	Wireless display compatible
BATÉRIA	EnergyPak Smart 625Wh EnergyPak Plus range extender compatible
RÁM	
VELKOSTI	XS, S, M, L, (XS: 27.5 / S-L: 29)
FARBY	Dark Iridescent/Black
RÁM	ALUXX SL-Grade Aluminum, Advanced Forged Composite Upper Rocker, 140mm Maestro Suspension System, 'Boost' 148x12QR, ISS
VIDLICA	Fox 36 Float Rhythm, 150mm travel, 44mm offset, EVOL, Grip Damper, Sweep adjust, Boost 110x15QR, e-optimized
TLMIČ	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position Lever, 185x52.5mm Trunnion mount, custom tuned
KOMPONENTY	
RIADIDLÁ	Giant Contact 35 Trail, 35x760-780mm (XS-S: 760 / M-L: 780)
GRIPY	Liv Supera Lock-on
PREDSTAVEC	Giant Contact SL 35
SEDLOVKA	Giant Contact Switch, dropper, 30,9mm (XS-S: 100, M:125, L:150)
SEDADLO	Liv Sylvia E+
PEDÁLE	Flatpedal
POHON	
RADENIE	Shimano SLX
PREŠMYKAČ	MRP 1X CS custom
PREHADZOVAČKA	Shimano Deore XT, 12-speed, Shadow+
BRZDY	Shimano Deore BR-M6120, 4-piston, hydraulic disc, 203mm
BRZDOVÉ PÁKY	Shimano Deore BL-M6100, 1-spec EV
KAZETA	Shimano CS-M6100-12, 10-51T, 12-speed
REŤAZ	KMC e.12 Turbo, EcoProteq, e-bike optimized
KLUKY	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (XS/S:160, M:165, L:170)
STREDOVÉ ZLOŽENIE	-

KOLESÁ	
RÁFIKY	Giant AM 29 / 27.5+, Tubeless ready, 30mm inner width
NÁBOJE	Shimano Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spling Drive Body Thru-axle
ŠPICE	Sapim E-Lite [r] Race [f]
PNEUMATIKY	Maxxis Assegai 29x2.6" foldable, Tubeless, EXO [F] Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+ [R] (XS: 27.5+ / S-L: 29)
DOPLNKY	Tubeless kit (liquid, valves, levers, manual, tool)
PRÍSLUŠENSTVO	
OSVETLENIE	-
ZAMKNÚŤ	-
NOSIČ	-

Cena: nová cena 4 029 € (stará cena 5 369 €)

## GEOMETRIA

RÁM	XS		S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dĺžka sedlovej trubky (mm)	385		405		435		460	
Uhol sedlovej trubky	74,5°	75,2°	76,0°	76,7°	76,0°	76,7°	76,0°	76,7°
Dĺžka hornej rámovej trubky (mm)	565	565	568	568	585	585	605	605
Dĺžka hlavovej trubky (mm)	95		95		100		110	
Uhol hlavovej trubky	65,0°	65,7°	65,8°	66,5°	65,8°	66,5°	65,8°	66,5°
Offset vidlice (mm)	44		44		44		44	
Trail (mm)	129,6	124,2	123,4	118,1	123,4	118,1	123,4	118,1
Rázvor (mm)	1190	1193	1195	1198	1213	1216	1235	1238
Dĺžka zadnej stavby (mm)	472	472	472	472	472	472	472	472
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	11	1	30	20	30	20	30	20
Stack - výška riadenia (mm)	585	579	608	602	613	607	622	616
Reach (mm)	403	412	416	426	432	442	450	459
Výška rámu od zeme (mm)	729	738	751	760	766	775	774	783
Šírka riaditok (mm)	750		750		780		780	
Dĺžka predstavca (mm)	40		40		50		60	
Dĺžka kľúk (mm)	160		165		165		170	
Rozmer kolies	27.5+		29"		29"		29"	

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.