



ŠPECIFIKÁCIE

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 80Nm, Powered by YAMAHA
OVĽÁDAČ	RideControl Ergo
OVĽÁDACIA JEDNOTKA	Wireless display compatible
BATÉRIA	EnergyPak Smart 625Wh EnergyPak Plus range extender compatible
RÁM	
VELKOSTI	XS, S, M, L, (XS: 27.5 / S-L: 29)
FARBY	Supernova/Black
RÁM	ALUXX SL-grade Aluminum, Advanced Forged Composite Upper Rocker, 140mm Maestro Suspension System, 'Boost' 148x12QR, ISS
VIDLICA	Rock Shox 35 Gold RL DebonAir, 150mm travel, 44mm offset, MotionControl™ rebound and lockout control, 15x110 Boost, Maxle Stealth, e-MTB optimized
TLMIČ	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position lever, 185x52.5mm Trunnion mount, custom tuned
KOMONENTY	
RIADIDLÁ	Giant Contact 35 Trail, 35x760~780mm (XS-S: 760 / M-L: 780)
GRIPY	Liv Supera Lock-on
PREDSTAVEC	Giant Contact SL 35
SEDLOVKA	Giant Contact Switch, dropper, 30,9mm (XS-S: 100, M:125, L:150)
SEDADLO	Liv Sylvia E+
PEDÁLE	Flatpedal
POHON	
RADENIE	Shimano Deore
PREŠMYKAČ	MRP 1X CS custom
PREHADZOVAČKA	Shimano Deore 12-speed
BRZDY	Shimano BR-M420, 4-piston, hydraulic disc, 203mm
BRZDOVÉ PÁKY	Shimano Deore BL-M4100, I-spec EV
KAZETA	Shimano CS-M6100-12, 10-51T, 12-speed
REŤAZ	KMC e.12 Turbo, EcoProteq, e-bike optimized
KLUKY	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (XS/S:160, M:165, L:170)
STREDOVÉ ZLOŽENIE	-

KOLESÁ	
RÁFIKY	Giant AM 29 / 27.5+, Tubeless ready, 30mm inner width
NÁBOJE	Giant eTracker Boost, Sealed cartridge bearing, 6-bolt, , [F] 110x15 [R] 148x12mm Thru-axle
ŠPICE	Sapim E-Lite [r] Race [f]
PNEUMATIKY	Maxxis Assegai 29x2.6" foldable, Tubeless, EXO [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+ [R] (XS: 27.5+ / S-L: 29)
DOPLNKY	Tubeless kit (liquid, valves, levers, manual, tool)
PRÍSLUŠENSTVO	
OSVETLENIE	-
ZAMKNÚŤ	-
NOSIČ	-

Cena: nová cena 3 749 € (stará cena 4 999 €)

GEOMETRIA

RÁM	XS		S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dĺžka sedlovej trubky (mm)	385	405	435	460				
Uhol sedlovej trubky	74,5° 75,2°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°				
Dĺžka hornej rámovej trubky (mm)	565 565	568 568	585 585	605 605				
Dĺžka hlavovej trubky (mm)	95	95	100	110				
Uhol hlavovej trubky	65,0° 65,7°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°				
Offset vidlice (mm)	44	44	44	44				
Trail (mm)	129,6 124,2	123,4 118,1	123,4 118,1	123,4 118,1				
Rázvor (mm)	1190 1193	1195 1198	1213 1216	1235 1238				
Dĺžka zadnej stavby (mm)	472 472	472 472	472 472	472 472				
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	11 1	30 20	30 20	30 20				
Stack - výška riadenia (mm)	585 579	608 602	613 607	622 616				
Reach (mm)	403 412	416 426	432 442	450 459				
Výška rámu od zeme (mm)	729 738	751 760	766 775	774 783				
Šírka riaditok (mm)	750	750	780	780				
Dĺžka predstavca (mm)	40	40	50	60				
Dĺžka kľúk (mm)	160	165	165	170				
Rozmer kolies	27.5+	29"	29"	29"				

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.