

# LANGMA ADVANCED 0



## SPECS

| FRAME            |                                                                                      |
|------------------|--------------------------------------------------------------------------------------|
| SIZES            | XXS, XS, S, M, L                                                                     |
| COLOURS          | Camel Silk/Chrome                                                                    |
| FRAME            | Advanced-grade Composite, 12x142mm thru-axle, disc                                   |
| FORK             | Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc |
| COMPONENTS       |                                                                                      |
| HANDLEBAR        | Liv Contact, XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm                     |
| GRIPS            | Liv Stratus Elite 2.0                                                                |
| STEM             | Giant Contact AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm            |
| SEATPOST         | Giant Variant, composite, -5/+15mm offset                                            |
| SADDLE           | Liv Approach                                                                         |
| DRIVETRAIN       |                                                                                      |
| SHIFTERS         | Shimano 105 Di2                                                                      |
| FRONT DERAILLEUR | Shimano 105 Di2 FD-R7150                                                             |
| REAR DERAILLEUR  | Shimano 105 Di2 RD-R7150                                                             |
| BRAKES           | Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors, [F] 160mm, [R] 140mm             |
| BRAKE LEVERS     | Shimano 105 Di2                                                                      |
| CASSETTE         | Shimano 105, 12-speed, 11x34                                                         |
| CHAIN            | KMC X12L-1                                                                           |
| CRANKSET         | Shimano 105, 36/52 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm             |
| BOTTOM BRACKET   | Shimano, press fit                                                                   |

| WHEELS             |                                                                                                                                 |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------|
| RIMS               | Giant SLR 2 40 WheelSystem, [F] 40mm, [R] 40mm                                                                                  |
| HUBS               | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T pawl driver, CenterLock, 12mm thru-axle |
| SPOKES             | Sapim Sprint                                                                                                                    |
| TIRES              | Giant Gavia Course 0, tubeless, 700x28c, folding                                                                                |
| EXTRAS             | tubeless prepared, 33mm max tire size                                                                                           |
| LIMITS             |                                                                                                                                 |
| MAX TIRE CLEARANCE | 33mm                                                                                                                            |

**Suggested Retail Price (CDN): \$5,199.00**

## FRAME GEOMETRY

| FRAME                    | XXS   | XS    | S     | M     | L     |
|--------------------------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm)    | 390   | 420   | 450   | 480   | 510   |
| Seat Tube Angle          | 75.0° | 75.0° | 74.5° | 74.0° | 73.5° |
| Top Tube Length (mm)     | 498   | 508   | 524   | 540   | 555   |
| Head Tube Length (mm)    | 105   | 120   | 135   | 155   | 175   |
| Head Tube Angle          | 70.0° | 71.0° | 72.0° | 72.5° | 72.5° |
| Fork Rake (mm)           | 49    | 49    | 49    | 49    | 49    |
| Trail (mm)               | 74    | 68    | 61    | 58    | 58    |
| Wheelbase (mm)           | 970   | 973   | 977   | 984   | 994   |
| Chain Stay Length (mm)   | 405   | 405   | 405   | 405   | 405   |
| Bottom Bracket Drop (mm) | 72    | 72    | 70    | 70    | 70    |
| Stack (mm)               | 499   | 517   | 532   | 553   | 572   |
| Reach (mm)               | 364   | 370   | 377   | 382   | 386   |
| Stand Over Height (mm)   | 685   | 707   | 736   | 763   | 783   |
| Handlebar Width (mm)     | 360   | 360   | 380   | 400   | 420   |
| Stem Length (mm)         | 80    | 80    | 90    | 100   | 110   |
| Crank Length (mm)        | 160   | 165   | 165   | 170   | 172.5 |

*All prices and specifications are subject to change without notice.*