

LANGMA ADVANCED 0



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
COLORS	Camel Silk/Chrome
FRAME	Advanced-grade Composite, 12x142mm thru-axle, disc
FORK	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Liv Contact, XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
STEM	Giant Contact AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SEATPOST	Giant Variant, composite, -5/+15mm offset
SADDLE	Liv Approach
DRIVETRAIN	
SHIFTERS	Shimano 105 Di2
FRONT DERAILLEUR	Shimano 105 Di2 FD-R7150
REAR DERAILLEUR	Shimano 105 Di2 RD-R7150
BRAKES	Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors, [F] 160mm, [R] 140mm
BRAKE LEVERS	Shimano 105 Di2
CASSETTE	Shimano 105, 12-speed, 11x34
CHAIN	KMC X12L-1
CRANKSET	Shimano 105, 36/52 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 2 40 WheelSystem, [F] 40mm, [R] 40mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T pawl driver, CenterLock, 12mm thru-axle
SPOKES	Sapim Sprint
TIRES	Giant Gavia Course 0, tubeless, 700x28c, folding
EXTRAS	tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

Recommended Retail Price: \$4,500.00

GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (inch)	15.4	16.5	17.7	18.9	20.1
Seat Tube Angle	75.0°	75.0°	74.5°	74.0°	73.5°
Top Tube Length (inch)	19.6	20	20.6	21.3	21.9
Head Tube Length (inch)	4.1	4.7	5.3	6.1	6.9
Head Tube Angle	70.0°	71.0°	72.0°	72.5°	72.5°
Fork Rake (inch)	1.9	1.9	1.9	1.9	1.9
Trail (inch)	2.9	2.7	2.4	2.3	2.3
Wheelbase (inch)	38.2	38.3	38.5	38.7	39.1
Chain Stay Length (inch)	15.9	15.9	15.9	15.9	15.9
Bottom Bracket Drop (inch)	2.8	2.8	2.8	2.8	2.8
Stack (inch)	19.6	20.4	20.9	21.8	22.5
Reach (inch)	14.3	14.6	14.8	15	15.2
Stand Over Height (inch)	27	27.8	29	30	30.8
Handlebar Width (inch)	14.2	14.2	15	15.7	16.5
Stem Length (inch)	3.1	3.1	3.5	3.9	4.3
Crank Length (inch)	6.3	6.5	6.5	6.7	6.8

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*