LANGMA ADVANCED 1 (PRO COMPACT)



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Meteorite Mist
FRAME	Advanced-grade Composite, 12x142mm thru-axle, disc
VOORVORK	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Liv Contact, XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
HANDVATTEN	Liv Stratus Elite 2.0
STUURPEN	Giant Contact AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
ZADELPEN	Giant Variant, composite, -5/+15mm offset
ZADEL	Liv Approach
AFMONTAGE	
SHIFTERS	Shimano 105 Di2
VOORDERAILLEUR	Shimano 105 Di2 FD-R7150
ACHTERDERAILLEUR	Shimano 105 Di2 RD-R7150
REMMEN	Shimano 105 Di2 hydraulic, Shimano SM-RT64 rotors, [F] 160mm, [R] 140mm
REMHENDELS	Shimano 105 Di2
CASSETTE	Shimano 105, 12-speed, 11x34
AANDRIJVING	KMC X12L-1
CRANKSET	Shimano 105, 36/52 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant P-R1, [F] 30mm, [R] 30mm
NAVEN	12mm thru-axle
SPAKEN	stainless
BANDEN	Giant Gavia Course 0, tubeless, 700x28c, folding
EXTRA'S	tubeless prepared, 33mm max tire size
LIMITS	
MAXIMALE BANDENVRIJHEID	33mm

Adviesprijs: € 3.499,00

GEOMETRIE

FRAME	XS	S	M	L
Zitbuis Lengte (mm)	420	450	480	510
Zitbuis Hoek	75,0°	74,5°	74,0°	73,5°
Frame Lengte (horizontaal) (mm)	508	524	540	555
Balhoofdbuis Lengte (mm)	120	135	155	175
Balhoofdbuis Hoek	71,0°	72,0°	72,5°	72,5°
Vork Sprong (mm)	49	49	49	49
Naloop (mm)	68	61	58	58
Wielbasis (mm)	973	977	984	994
Liggende achtervork lengte (mm)	405	405	405	405
Bottom Bracket Drop (mm)	72	70	70	70
Stack (mm)	517	532	553	572
Reach (mm)	370	377	382	386
Stand Over Height (mm)	707	736	763	783
Stuur breedte (mm)	360	380	400	420
Stuurpen Lengte (mm)	80	90	100	110
Cranklengte (mm)	165	165	170	172,5

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.