LANGMA ADVANCED 1 (PRO COMPACT)



SPECS

RAMME	
STØRRELSE	XXS, XS, S, M, L
FARGE	Meteorite Mist
RAMME	Advanced-grade Composite, 12x142mm thru-axle, disc
GAFFEL	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
DEMPER	N/A
KOMPONENTER	
STYRE	Liv Contact, XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
STYRSTEM	Giant Contact AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SETEPINNE	Giant Variant, composite, -5/+15mm offset
SADEL	Liv Approach
DRIVVERK	
GIRHENDLER	Shimano 105 Di2
FRONTGIR	Shimano 105 Di2 FD-R7150
BAKGIR	Shimano 105 Di2 RD-R7150
BREMSER	Shimano 105 Di2 hydraulic, Shimano SM-RT64 rotors, [F] 160mm, [R] 140mm
BREMSEHENDLER	Shimano 105 Di2
KASSETT	Shimano 105, 12-speed, 11x34
KJEDE	KMC X12L-1
KRANK	Shimano 105, 36/52 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

HJUL	
FELG	Giant P-R1, [F] 30mm, [R] 30mm
NAV	12mm thru-axle
EIKE	stainless
DEKK	Giant Gavia Course 0, tubeless, 700x28c, folding
EXTRAS	tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRI

RAMME	XXS	XS	S	M	L
Seat Tube Length (mm)	390	420	450	480	510
Seat Tube Angle	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	498	508	524	540	555
Head Tube Length (mm)	105	120	135	155	175
Head Tube Angle	70,0°	71,0°	72,0°	72,5°	72,5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	74	68	61	58	58
Wheelbase (mm)	970	973	977	984	994
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	70
Stack (mm)	499	517	532	553	572
Reach (mm)	364	370	377	382	386
Stand Over Height (mm)	685	707	736	763	783
Handlebar Width (mm)	360	360	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	160	165	165	170	172,5

Alle spesifikasjonene kan endres uten varsel.