LANGMA ADVANCED 1 (PRO COMPACT)



SPECS

QUADRO	
TAMANHOS	XXS, XS, S, M, L
CORES	Meteorite Mist
QUADRO	Advanced-grade Composite, 12x142mm thru-axle, disc
FORQUILHA	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
AMORTECEDORES	N/A
COMPONENTES	
GUIADOR	Liv Contact, XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
PUNHOS	Liv Stratus Elite 2.0
AVANÇO	Giant Contact AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
ESPIGÃO DE SELIM	Giant Variant, composite, -5/+15mm offset
SELIM	Liv Approach
TRANSMISSÃO	
MANETES	Shimano 105 Di2
DESVIADOR DIANTEIRO	Shimano 105 Di2 FD-R7150
DESVIADOR TRASEIRO	Shimano 105 Di2 RD-R7150
TRAVÕES	Shimano 105 Di2 hydraulic, Shimano SM-RT64 rotors, [F] 160mm, [R] 140mm
MANÍPULOS DOS TRAVÕES	Shimano 105 Di2
CASSETE	Shimano 105, 12-speed, 11x34
CORRENTE	KMC X12L-1
CONJUNTO PEDALEIRO	Shimano 105, 36/52 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
MOVIMENTO CENTRAL	Shimano, press fit

RODAS	
AROS	Giant P-R1, [F] 30mm, [R] 30mm
CUBOS	12mm thru-axle
RAIOS	stainless
PNEUS	Giant Gavia Course 0, tubeless, 700x28c, folding
EXTRAS	tubeless prepared, 33mm max tire size
LIMITES	
FOLGA MÁXIMA DO PNEU	33mm

Preço: 2 899,00 €

GEOMETRIA

QUADRO	XXS	XS	S	M
Comprimento do tubo do assento (mm)	390	420	450	480
Ângulo do tubo do assento	75,0°	75,0°	74,5°	74,0°
Comprimento do tubo superior (mm)	498	508	524	540
Comprimento do tubo principal (mm)	105	120	135	155
Ângulo do tubo principal	70,0°	71,0°	72,0°	72,5°
Garfo ancinho (mm)	49	49	49	49
Trilha (mm)	74	68	61	58
distância entre eixos (mm)	970	973	977	984
Comprimento Chain Stay (mm)	405	405	405	405
Suporte inferior (mm)	72	72	70	70
Pilha (mm)	499	517	532	553
Alcançar (mm)	364	370	377	382
Altura do standover (mm)	685	707	736	763
Largura do guidão (mm)	360	360	380	400
Comprimento da haste (mm)	80	80	90	100
Comprimento da Manivela (mm)	160	165	165	170

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.