LANGMA ADVANCED 1 (PRO COMPACT)



SPECS

CADRU	
MARIMI	XXS, XS, S, M, L
CULORI	Meteorite Mist
CADRU	Advanced-grade Composite, 12x142mm thru-axle, disc
FURCA	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
SOC	N/A
COMPONENTE	
GHIDON	Liv Contact, XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
PIPA	Giant Contact AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
TIJA SA	Giant Variant, composite, -5/+15mm offset
SA	Liv Approach
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano 105 Di2
SCHIMBATOR FATA	Shimano 105 Di2 FD-R7150
SCHIMBATOR SPATE	Shimano 105 Di2 RD-R7150
FRANE	Shimano 105 Di2 hydraulic, Shimano SM-RT64 rotors, [F] 160mm, [R] 140mm
MANETE FRANA	Shimano 105 Di2
PINIOANE	Shimano 105, 12-speed, 11x34
LANT	KMC X12L-1
ANGRENAJ	Shimano 105, 36/52 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

ROTI	
JANTE	Giant P-R1, [F] 30mm, [R] 30mm
BUTUCI	12mm thru-axle
SPITE	stainless
ANVELOPE	Giant Gavia Course 0, tubeless, 700x28c, folding
EXTRAS	tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRIE

CADRU	XXS	XS	S	M	L
Seat Tube Length (mm)	390	420	450	480	510
Seat Tube Angle	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	498	508	524	540	555
Head Tube Length (mm)	105	120	135	155	175
Head Tube Angle	70,0°	71,0°	72,0°	72,5°	72,5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	74	68	61	58	58
Wheelbase (mm)	970	973	977	984	994
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	70
Stack (mm)	499	517	532	553	572
Reach (mm)	364	370	377	382	386
Stand Over Height (mm)	685	707	736	763	783
Handlebar Width (mm)	360	360	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	160	165	165	170	172,5

Toate specificatiile enumerate se pot schimba fara notificare prealabila.