# LANGMA ADVANCED 1 (PRO COMPACT)



## SPECS

| FRAME | |
|---|---|
| **SIZES** | XXS, XS, S, M, L |
| **COLORS** | Meteorite Mist |
| **FRAME** | Advanced-grade Composite, 12x142mm thru-axle, disc |
| **FORK** | Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc |
| **SHOCK** | N/A |
| **COMPONENTS** | |
| **HANDLEBAR** | Liv Contact, XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm |
| **GRIPS** | Liv Stratus Elite 2.0 |
| **STEM** | Giant Contact AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm |
| **SEATPOST** | Giant Variant, composite, -5/+15mm offset |
| **SADDLE** | Liv Approach |
| **DRIVETRAIN** | |
| **SHIFTERS** | Shimano 105 Di2 |
| **FRONT DERAILLEUR** | Shimano 105 Di2 FD-R7150 |
| **REAR DERAILLEUR** | Shimano 105 Di2 RD-R7150 |
| **BRAKES** | Shimano 105 Di2 hydraulic, Shimano SM-RT64 rotors, [F] 160mm, [R] 140mm |
| **BRAKE LEVERS** | Shimano 105 Di2 |
| **CASSETTE** | Shimano 105, 12-speed, 11x34 |
| **CHAIN** | KMC X12L-1 |
| **CRANKSET** | Shimano 105, 36/52 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm |
| **BOTTOM BRACKET** | Shimano, press fit |

| WHEELS | |
|---|---|
| **RIMS** | Giant P-R1, [F] 30mm, [R] 30mm |
| **HUBS** | 12mm thru-axle |
| **SPOKES** | stainless |
| **TIRES** | Giant Gavia Course 0, tubeless, 700x28c, folding |
| **EXTRAS** | tubeless prepared, 33mm max tire size |
| **LIMITS** | |
| **MAX TIRE CLEARANCE** | 33mm |

## GEOMETRY

| FRAME | XXS | XS | S | M | L |
|---|---|---|---|---|---|
| Seat Tube Length (mm) | 390 | 420 | 450 | 480 | 510 |
| Seat Tube Angle | 75.0° | 75.0° | 74.5° | 74.0° | 73.5° |
| Top Tube Length (mm) | 498 | 508 | 524 | 540 | 555 |
| Head Tube Length (mm) | 105 | 120 | 135 | 155 | 175 |
| Head Tube Angle | 70.0° | 71.0° | 72.0° | 72.5° | 72.5° |
| Fork Rake (mm) | 49 | 49 | 49 | 49 | 49 |
| Trail (mm) | 74 | 68 | 61 | 58 | 58 |
| Wheelbase (mm) | 970 | 973 | 977 | 984 | 994 |
| Chain Stay Length (mm) | 405 | 405 | 405 | 405 | 405 |
| Bottom Bracket Drop (mm) | 72 | 72 | 70 | 70 | 70 |
| Stack (mm) | 499 | 517 | 532 | 553 | 572 |
| Reach (mm) | 364 | 370 | 377 | 382 | 386 |
| Stand Over Height (mm) | 685 | 707 | 736 | 763 | 783 |
| Handlebar Width (mm) | 360 | 360 | 380 | 400 | 420 |
| Stem Length (mm) | 80 | 80 | 90 | 100 | 110 |
| Crank Length (mm) | 160 | 165 | 165 | 170 | 172.5 |

*All specifications listed are subject to change without notice.*