

LANGMA ADVANCED 1 QOM



SPECIFIKACIJE

OKVIR	
VELIČINE	XXS, XS, S, M, L
BOJE	Mechanic Rose, Sunset Ivory
OKVIR	Advanced-Grade Composite, 12x142mm thru-axle, disc
VILICA	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
KOMPONENTE	
VOLAN	Liv Contact XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
LULA VOLANA	Giant Contact AeroLight XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
CIJEV SJEDALA	Giant Variant, composite, -5/+15mm offset
SJEDALO	Liv Approach
POGON	
RUČICE MJENJAČA	Shimano 105 Di2
PREDNJI MJENJAČ	Shimano 105 Di2 FD-R7150
STRAŽNJI MJENJAČ	Shimano 105 Di2 RD-R7150
KOČNICE	Shimano 105 Di2 hydraulic, Giant MPH rotors [F] 160mm, [R] 140mm
RUČICE KOČNICA	Shimano 105 Di2
KAZETA	Shimano 105, 12-speed, 11x36
LANAC	KMC X12L-1
POGON	Shimano 105, 34/50 XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
OSOVINA POGONA (BB)	Shimano, press fit

KOTAČI	
OBRUČI	Giant P-R2, [F] 25mm, [R] 25mm
NABE	12mm thru-axle
ŽBICE	stainless
GUME	Giant Gavia Course 1, tubeless, 700x25c (28mm), folding
DODACI	tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRIJA

OKVIR	XXS	XS	S	M	L
Dužina cijevi sjedala (mm)	390	420	450	480	510
Kut cijevi sjedala	75,0°	75,0°	74,5°	74,0°	73,5°
Dužina gornje cijevi (mm)	498	508	524	540	555
Dužina prednje cijevi (mm)	105	120	135	155	175
Kut vilice	70,0°	71,0°	72,0°	72,5°	72,5°
Zakrivljenost vilice (offset) (mm)	49	49	49	49	49
Staza (mm)	74	68	61	58	58
Međuosovinski razmak kotača (mm)	970	973	977	984	994
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	405	405	405	405	405
Položaj osovine pogona (mm)	72	72	69,5	69,5	69,5
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	499	517	532	553	572
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	364	370	377	382	386
Prekoračna visina (mm)	685	707	736	763	783
Širina volana (mm)	360	360	380	400	420
Dužina lule volana (mm)	80	80	90	100	110
Dužina poluge pedale (mm)	165	165	170	170	172,5
Veličina kotača	700C	700C	700C	700C	700C

Sve navedene specifikacije podložne su promjeni bez prethodne najave.