LANGMA ADVANCED 1 QOM



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
COLORS	Meteorite Mist
FRAME	Advanced-grade Composite, 12x142mm thru-axle, disc
FORK	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv Contact, XXS: 360mm, XS: 360mm, S: 380mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
STEM	Giant Contact AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SEATPOST	Giant Variant, composite, -5/+15mm offset
SADDLE	Liv Approach
PEDALS	platform pedal [GCS,GTS], N/A [all other GSC]
DRIVETRAIN	
SHIFTERS	Shimano 105 Di2
FRONT DERAILLEUR	Shimano 105 Di2 FD-R7150
REAR DERAILLEUR	Shimano 105 Di2 RD-R7150
BRAKES	Shimano 105 Di2 hydraulic, Shimano SM-RT64 rotors, [F] 160mm, [R] 140mm
BRAKE LEVERS	Shimano 105 Di2
CASSETTE	Shimano 105, 12-speed, 11x36
CHAIN	KMC X12L-1
CRANKSET	Shimano 105, 34/50 XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant P-R1, [F] 25mm, [R] 25mm
HUBS	12mm thru-axle
SPOKES	stainless
TIRES	Giant Gavia Course 0, tubeless, 700x28c, folding
EXTRAS	tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	390	420	450	480	510
Seat Tube Angle	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	498	508	524	540	555
Head Tube Length (mm)	105	120	135	155	175
Head Tube Angle	70,0°	71,0°	72,0°	72,5°	72,5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	74	68	61	58	58
Wheelbase (mm)	970	973	977	984	994
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	70
Stack (mm)	499	517	532	553	572
Reach (mm)	364	370	377	382	386
Stand Over Height (mm)	685	707	736	763	783
Handlebar Width (mm)	360	360	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	160	165	165	170	172,5

All specifications listed are subject to change without notice.