

LANGMA ADVANCED 2-QOM



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
FRAME	Advanced-Grade Composite 12x142mm thru-axle, Disc
FORK	Advanced-Grade Composite, Full-Composite OverDrive Steerer, 12x100mm thru-axle, Disc
COMPONENTS	
HANDLEBAR	Liv Contact, 31.8, Reach 68mm, Drop 120mm (360mm-380mm) Reach 72mm, Drop 125mm (400mm-440mm) XXS: 360, XS: 360, S: 380, M: 400, L: 420
GRIPS	Liv Stratus Elite 2.0
STEM	Giant Contact Aerolight, -10° XXS: 80, XS: 80, S: 90, M: 100, L: 110
SEATPOST	Giant Variant, Composite
SADDLE	Liv Approach
DRIVETRAIN	
SHIFTERS	Shimano 105 HRD
FRONT DERAILLEUR	Shimano 105
REAR DERAILLEUR	Shimano 105
BRAKES	Shimano 105 HRD, Shimano SM-RT64, [F]160 [R]140
BRAKE LEVERS	Shimano 105 HRD
CASSETTE	Shimano 105, 11x36
CHAIN	KMC X12
CRANKSET	Shimano 105, 34/50 XXS: 160, XS: 165, S: 165, M: 170, L: 172.5
BOTTOM BRACKET	Shimano, PressFit RS500

WHEELS	
RIMS	Giant P-R1 Disc 12mm Thru-Axle
TIRES	Giant Gavia COURSE 0 Tubeless, 700x30C, 170 TPI , Folding
EXTRAS	tubeless prepared
LIMITS	
MAX TIRE CLEARANCE	700x33mm

Suggested Retail Price (CDN): \$3,799.00

FRAME GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	390	420	450	480	510
Seat Tube Angle	75.0°	75.0°	74.5°	74.0°	73.5°
Top Tube Length (mm)	498	508	524	540	555
Head Tube Length (mm)	105	120	135	155	175
Head Tube Angle	70.0°	71.0°	72.0°	72.5°	72.5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	74	68	61	58	58
Wheelbase (mm)	970	973	977	984	994
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	69.5	69.5	69.5
Stack (mm)	499	517	532	553	572
Reach (mm)	364	370	377	382	386
Stand Over Height (mm)	685	707	736	763	783
Handlebar Width (mm)	360	360	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	165	165	170	170	172.5
Wheel Size	700C	700C	700C	700C	700C

All prices and specifications are subject to change without notice.