

LANGMA ADVANCED DISC 1+



SPECIFICATIES

FRAME	
MATEN	XXS, XS, S, M, L
KLEUREN	Cold Iron
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc
VOORVORK	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Liv Contact XXS:36cm, XS:36cm, S:38cm, M:40cm, L:42cm
HANDVATTEN	Liv All Condition
STUURPEN	Giant Contact XXS:80mm, XS:80mm, S:90mm, M:100mm, L:110mm
ZADELPEEN	Giant Variant, composite XXS:357mm, XS:357mm, S:357mm, M:357mm, L:357mm
ZADEL	Liv Approach
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	Shimano Ultegra
VOORDERAILLEUR	Shimano Ultegra
ACHTERDERAILLEUR	Shimano Ultegra
REMMEN	Shimano Ultegra hydraulic, Shimano rotors [F]160mm, [R]140mm
REMHENDELS	Shimano Ultegra hydraulic
CASSETTE	Shimano 105, 11-speed, 11x30
AANDRIJVING	KMC X11SL-1
CRANKSET	Shimano Ultegra, 36/52 XXS:165mm, XS:165mm, S:170mm, M:170mm, L:172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant SLR-2 36 Disc WheelSystem
NAVEN	Giant SLR-2 36 Disc WheelSystem, 12mm thru-axle
SPAKEN	Giant SLR-2 36 Disc WheelSystem
BANDEN	Giant Course 1, tubeless, 700x25c (28mm), folding
EXTRA'S	tubeless prepared, 32mm max tire size

Adviesprijs: € 3.499,00

GEOMETRIE

FRAME	XXS	XS	S	M	L
Zitbuis Lengte (mm)	390	420	450	480	510
Zitbuis Hoek	75,0°	75,0°	74,5°	74,0°	73,5°
Frame Lengte (horizontaal) (mm)	498	508	524	540	555
Balhoofdbuis Lengte (mm)	105	120	135	155	175
Balhoofdbuis Hoek	70,0°	71,0°	72,0°	72,5°	72,5°
Vork Sprong (mm)	49	49	49	49	49
Naloop (mm)	74,3	67,8	61,4	58,2	58,2
Wielbasis (mm)	970,4	973	977,2	984,2	995,5
Liggende achtersvork lengte (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	69,5	69,5	67
Stack (mm)	498,8	516,5	531,8	552,6	569,2
Reach (mm)	364,4	369,6	376,5	381,5	386,4
Stand Over Height (mm)	680	700	730	760	790
Stuur breedte (mm)	360	360	380	400	420
Stuurpen Lengte (mm)	80	80	90	100	110
Cranklengte (mm)	165	165	170	170	172,5
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.