

# LANGMA ADVANCED PRO 0 PC



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLOURS</b>	Ocean Twilight/Chrome
<b>FRAME</b>	Advanced-Grade Composite, 12x142mm thru-axle, disc
<b>FORK</b>	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
<b>HANDLEBAR</b>	Liv Contact SLR XS:34/36cm, S:36/38cm, M:38/40cm, L:39/42cm
<b>GRIPS</b>	Liv Stratus Elite 2.0
<b>STEM</b>	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, L:110mm
<b>SEATPOST</b>	Giant Variant, composite, -5/+15mm offset
<b>SADDLE</b>	Liv Alacra SL
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Ultegra Di2
<b>FRONT DERAILLEUR</b>	Shimano Ultegra Di2 FD-R8150
<b>REAR DERAILLEUR</b>	Shimano Ultegra Di2 RD-R8150
<b>BRAKES</b>	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
<b>BRAKE LEVERS</b>	Shimano Ultegra Di2
<b>CASSETTE</b>	Shimano Ultegra, 12-speed, 11x34
<b>CHAIN</b>	Shimano Ultegra
<b>CRANKSET</b>	Shimano Ultegra, 36/52 with Giant Power Pro power meter XS:165mm, S:170mm, M:170mm, L:172.5mm
<b>BOTTOM BRACKET</b>	Shimano, press fit

WHEELS	
<b>RIMS</b>	Giant SLR 0 40 WheelSystem, [F] 40mm, [R] 40mm
<b>HUBS</b>	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Giant Aero Carbon Spoke
<b>TYRES</b>	CADEX Race GC, tubeless, 700x28c (28mm), folding
<b>EXTRAS</b>	Computer mount, tubeless prepared, 33mm max tyre size
LIMITS	
<b>MAX TYRE CLEARANCE</b>	33mm

**Price: \$8,199.00**

## GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	420	450	480	510
Seat Tube Angle	75.0°	74.5°	74.0°	73.5°
Top Tube Length (mm)	508	524	540	555
Head Tube Length (mm)	120	135	155	175
Head Tube Angle	71.0°	72.0°	72.5°	72.5°
Fork Rake (mm)	49	49	49	49
Trail (mm)	68	61	58	58
Wheelbase (mm)	973	977	984	994
Chain Stay Length (mm)	405	405	405	405
Bottom Bracket Drop (mm)	72	69.5	69.5	69.5
Stack (mm)	517	532	553	572
Reach (mm)	370	377	382	386
Stand Over Height (mm)	707	736	763	783
Stem Length (mm)	80	90	100	110
Crank Length (mm)	165	170	170	172.5
Wheel Size	700C	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.