

LANGMA ADVANCED PRO 0-PC



SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Desert Pearl
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc
FORK	Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Liv Contact SLR XS:34/36cm, S:36/38cm, M:38/40cm
GRIPS	Stratus Elite 3.0
STEM	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm
SEATPOST	Giant Variant, composite, -5/+15mm offset
SADDLE	Liv Alacra SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Ultegra Di2 ST-R8170
FRONT DERAILLEUR	Shimano Ultegra Di2 FD-R8150
REAR DERAILLEUR	Shimano Ultegra Di2 RD-R8150
BRAKES	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
BRAKE LEVERS	Shimano Ultegra Di2 hydraulic
CASSETTE	Shimano Ultegra, 12-speed, 11x34
CHAIN	Shimano CN-M8100
CRANKSET	Shimano Ultegra, 36/52 with Giant Power Pro power meter XS:165mm, S:165mm, M:170mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 0 40 WheelSystem, [F] 40mm, [R] 40mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 21H [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 24H
SPOKES	Giant Aero Carbon Spoke
TYRES	CADEX Race GC, tubeless, 700x30c (30mm), folding
EXTRAS	Computer mount, tubeless prepared
LIMITS	
MAX TYRE CLEARANCE	33mm

Price: \$7,999.00

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	420	450	480
Seat Tube Angle	75.0°	74.5°	74.0°
Top Tube Length (mm)	508	524	540
Head Tube Length (mm)	120	135	155
Head Tube Angle	71.0°	72.0°	72.5°
Fork Rake (mm)	49	49	49
Trail (mm)	68	61	58
Wheelbase (mm)	973	977	984
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	72	70	70
Stack (mm)	517	532	553
Reach (mm)	370	377	382
Stand Over Height (mm)	707	736	763
Stem Length (mm)	80	90	100
Crank Length (mm)	165	165	170

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.