

LANGMA ADVANCED PRO 0 PC



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
COLOURS	Ocean Twilight/Chrome
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc
FORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Liv Contact SLR 31.8mm, 8-degree flare drop XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
GRIPS	Liv Stratus Elite 2.0
STEM	Giant Contact SL AeroLight XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SEATPOST	Giant Variant, composite, -5/+15mm offset
SADDLE	Liv Alacra SL
DRIVETRAIN	
SHIFTERS	Shimano Ultegra Di2
FRONT DERAILLEUR	Shimano Ultegra Di2 FD-R8150
REAR DERAILLEUR	Shimano Ultegra Di2 RD-R8150
BRAKES	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
BRAKE LEVERS	Shimano Ultegra Di2
CASSETTE	Shimano Ultegra, 12-speed, 11x34
CHAIN	Shimano CN-M8100
CRANKSET	Shimano Ultegra, 36/52 with Giant Power Pro power meter XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 0 40 WheelSystem, [F] 40mm, [R] 40mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Giant Aero Carbon Spoke
TIRES	CADEX Race GC, tubeless, 700x28c (28mm), folding
EXTRAS	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

Suggested Retail Price (CDN): \$7,999.00

FRAME GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	390	420	450	480	510
Seat Tube Angle	75.0°	75.0°	74.5°	74.0°	73.5°
Top Tube Length (mm)	498	508	524	540	555
Head Tube Length (mm)	105	120	135	155	175
Head Tube Angle	70.0°	71.0°	72.0°	72.5°	72.5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	74	68	61	58	58
Wheelbase (mm)	970	973	977	984	994
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	69.5	69.5	69.5
Stack (mm)	499	517	532	553	572
Reach (mm)	364	370	377	382	386
Stand Over Height (mm)	685	707	736	763	783
Handlebar Width (mm)	360	360	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	165	165	170	170	172.5
Wheel Size	700C	700C	700C	700C	700C

All prices and specifications are subject to change without notice.