LANGMA ADVANCED PRO 0 (PRO COMPACT)



SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, L
FARVER	Thundercloud
RAMME	Advanced-grade Composite, 12x142mm thru-axle, disc
FORGAFFEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
BAGDÆMPER	N/A
KOMPONENTER	
STYR	Liv Contact SLR , 31.8mm, 8-degree flare drop, XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
GREB / STYRBÅND	Liv Stratus Elite 2.0
FREMPIND	Giant Contact SL AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SADELPIND	Giant Variant, composite, -5/+15mm offset
SADEL	Liv Alacra SL
PEDALER	platform pedal [GCS,GTS], N/A [all other GSC]
GEARGRUPPE	
SKIFTEGREB	Shimano Ultegra Di2
FORSKIFTER	Shimano Ultegra Di2 FD-R8150
BAGSKIFTER	Shimano Ultegra Di2 RD-R8150
BREMSER	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors, [F]160mm, [R]140mm
BREMSEGREB	Shimano Ultegra Di2
KASSETTE	Shimano Ultegra, 12-speed, 11x34
KÆDE	Shimano CN-M8100
KRANKSÆT	Shimano Ultegra, 36/52 with Giant Power Pro power meter XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
KRANKBOKS	Shimano, press fit

HJUL	
FÆLGE	Giant SLR 0 40 WheelSystem, [F] 40mm, [R] 40mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
EGER	Giant Aero Carbon Spoke
DÆK	CADEX Road Race GC, tubeless, 700x28c, folding
EKSTRA	computer mount, tubeless prepared, 33mm max tire size
GRÆNSER	
MAX DÆKSTØRRELSE	33mm

Pris: 51.299,00 kr.

GEOMETRI

RAMME	XS	S	M	L
Sadelrørslængde (mm)	420	450	480	510
Sadelrørsvinkel	75,0°	74,5°	74,0°	73,5°
Overrørslængde (mm)	508	524	540	555
Kronrørslængde (mm)	120	135	155	175
Kronrøsvinkel	71,0°	72,0°	72,5°	72,5°
Forgaffel fremspring (rake) (mm)	49	49	49	49
Sti (mm)	68	61	58	58
Akselafstand (mm)	973	977	984	994
Kædestagslængde (mm)	405	405	405	405
Krankboks drop (mm)	72	70	70	70
Stack (mm)	517	532	553	572
Reach (mm)	370	377	382	386
Skridthøjde (mm)	707	736	763	783
Styrbredde (mm)	360	380	400	420
Frempindslængde (mm)	80	90	100	110
Pedalarmslængde (mm)	165	165	170	172,5

Alle de anførte specifikationer kan ændres uden varsel.