

# LANGMA ADVANCED PRO 0 (PRO COMPACT)



## SPECIFIKACIJE

OKVIR	
VELIKOSTI	XXS, XS, S, M, L
BARVE	Thundercloud
OKVIR	Advanced-grade Composite, 12x142mm thru-axle, disc
VILICE	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Liv Contact SLR, 31.8mm, 8-degree flare drop, XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
GRIPS	Liv Stratus Elite 2.0
OPORA KRMILA	Giant Contact SL AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
OPORA SEDEŽA	Giant Variant, composite, -5/+15mm offset
SEDEŽ	Liv Alacra SL
PEDALA	platform pedal [GCS,GTS], N/A [all other GSC]
POGON	
PRESTAVNE ROČICE	Shimano Ultegra Di2
PREDNJI MENJALNIK	Shimano Ultegra Di2 FD-R8150
ZADNJI MENJALNIK	Shimano Ultegra Di2 RD-R8150
ZAVORE	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors, [F]160mm, [R]140mm
ZAVORNE ROČICE	Shimano Ultegra Di2
VERIŽNIK	Shimano Ultegra, 12-speed, 11x34
VERIGA	Shimano CN-M8100
GONILKE Z VERIŽNIKI	Shimano Ultegra, 36/52 with Giant Power Pro power meter XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant SLR 0 40 WheelSystem, [F] 40mm, [R] 40mm
PESTA	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
NAPERE	Giant Aero Carbon Spoke
PLAŠČI	CADEX Road Race GC, tubeless, 700x28c, folding
DODATKI	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

## GEOMETRIJA

OKVIR	XXS	XS	S	M	L
Dolžina sedežne cevi (mm)	390	420	450	480	510
Kot sedežne cevi	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	498	508	524	540	555
Višina glave okvirja (mm)	105	120	135	155	175
Krmlini kot	70,0°	71,0°	72,0°	72,5°	72,5°
Zamik vpetja osi (mm)	49	49	49	49	49
Trail (mm)	74	68	61	58	58
Medosna razdalja (mm)	970	973	977	984	994
Dolžina cevi ob verigi (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	70
Oddaljenost zgornje cevi od gonilne osi (mm)	499	517	532	553	572
Doseg (mm)	364	370	377	382	386
Višina zgornje cevi (mm)	685	707	736	763	783
Širina krmila (mm)	360	360	380	400	420
Dolžina opore krmila (mm)	80	80	90	100	110
Dolžina gonilke (mm)	160	165	165	170	172,5

Vse navedene specifikacije se lahko spremenijo brez obvestila.