

LANGMA ADVANCED PRO 0 QOM



SPECS

RAMME	
STØRRELSE	XXS, XS, S, M, L
FARGE	Thundercloud
RAMME	Advanced-grade Composite, 12x142mm thru-axle, disc
GAFFEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	Liv Contact SLR, 31.8mm, 8-degree flare drop, XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
GRIPS	Liv Stratus Elite 2.0
STYRSTEM	Giant Contact SL AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SETEPINNE	Giant Variant, composite, -5/+15mm offset
SADEL	Liv Alacra SL
DRIVVERK	
GIRHENDLER	Shimano Ultegra Di2
FRONTGIR	Shimano Ultegra Di2 FD-R8150
BAKGIR	Shimano Ultegra Di2 RD-R8150
BREMSER	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors, [F]160mm, [R]140mm
BREMSEHENDLER	Shimano Ultegra Di2
KASSETT	Shimano Ultegra, 12-speed, 11x34
KJEDE	Shimano CN-M8100
KRANK	Shimano Ultegra, 34/50 with Giant Power Pro power meter XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

HJUL	
FELG	Giant SLR 0 40 WheelSystem, [F] 40mm, [R] 40mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
EIKE	Giant Aero Carbon Spoke
DEKK	CADEX Road Race GC, tubeless, 700x28c, folding
EXTRAS	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRI

RAMME	XXS	XS	S	M	L
Seat Tube Length (mm)	390	420	450	480	510
Seat Tube Angle	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	498	508	524	540	555
Head Tube Length (mm)	105	120	135	155	175
Head Tube Angle	70,0°	71,0°	72,0°	72,5°	72,5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	74	68	61	58	58
Wheelbase (mm)	970	973	977	984	994
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	70
Stack (mm)	499	517	532	553	572
Reach (mm)	364	370	377	382	386
Stand Over Height (mm)	685	707	736	763	783
Handlebar Width (mm)	360	360	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	160	165	165	170	172,5

Alle spesifikasjonene kan endres uten varsel.