

LANGMA ADVANCED PRO 1 AXS



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
COLOURS	Aurora Noise
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc
FORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Liv Contact SL 31.8mm, 8-degree flare drop XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
GRIPS	Liv Stratus Elite 2.0
STEM	Giant Contact SL AeroLight XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SEATPOST	Giant Variant, composite, -5/+15mm offset
SADDLE	Liv Alacra SL
DRIVETRAIN	
SHIFTERS	SRAM Rival AXS
FRONT DERAILLEUR	SRAM Rival AXS
REAR DERAILLEUR	SRAM Rival AXS
BRAKES	SRAM Rival eTap hydraulic, SRAM PaceLine rotors [F] 160mm, [R] 140mm
BRAKE LEVERS	SRAM Rival AXS
CASSETTE	SRAM Rival, 12-speed, 10x36
CHAIN	SRAM Rival D1
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant SLR 1 40 WheelSystem, [F] 40mm, [R] 40mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TIRES	Giant Gavia Course 0, tubeless, 700x25c (28mm), folding
EXTRAS	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

Suggested Retail Price (CDN): \$6,899.00

FRAME GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	420	450	480
Seat Tube Angle	75.0°	74.5°	74.0°
Top Tube Length (mm)	508	524	540
Head Tube Length (mm)	120	135	155
Head Tube Angle	71.0°	72.0°	72.5°
Fork Rake (mm)	49	49	49
Trail (mm)	68	61	58
Wheelbase (mm)	973	977	984
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	72	69.5	69.5
Stack (mm)	517	532	553
Reach (mm)	370	377	382
Stand Over Height (mm)	707	736	763
Handlebar Width (mm)	360	380	400
Stem Length (mm)	80	90	100
Crank Length (mm)	165	170	170
Wheel Size	700C	700C	700C

All prices and specifications are subject to change without notice.