



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
COLORS	Aurora Noise
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc
FORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Liv Contact SL 31.8mm, 8-degree flare drop XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
GRIPS	Liv Stratus Elite 2.0
STEM	Giant Contact SL AeroLight XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SEATPOST	Giant Variant, composite, -5/+15mm offset
SADDLE	Liv Alacra SL
DRIVETRAIN	
SHIFTERS	SRAM Rival AXS
FRONT DERAILLEUR	SRAM Rival AXS
REAR DERAILLEUR	SRAM Rival AXS
BRAKES	SRAM Rival eTap hydraulic, SRAM PaceLine rotors [F] 160mm, [R] 140mm
BRAKE LEVERS	SRAM Rival AXS
CASSETTE	SRAM Rival, 12-speed, 10x36
CHAIN	SRAM Rival D1
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant SLR 1 40 WheelSystem, [F] 40mm, [R] 40mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TIRES	Giant Gavia Course 0, tubeless, 700x25c (28mm), folding
EXTRAS	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	390	420	450	480	510
Seat Tube Angle	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	498	508	524	540	555
Head Tube Length (mm)	105	120	135	155	175
Head Tube Angle	70,0°	71,0°	72,0°	72,5°	72,5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	74	68	61	58	58
Wheelbase (mm)	970	973	977	984	994
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	69,5	69,5	69,5
Stack (mm)	499	517	532	553	572
Reach (mm)	364	370	377	382	386
Stand Over Height (mm)	685	707	736	763	783
Handlebar Width (mm)	360	360	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	165	165	170	170	172,5
Wheel Size	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.