

LANGMA ADVANCED PRO 1 AXS



SPECS

RAM	
STORLEKAR	XXS, XS, S, M, L
FÄRGER	Aurora Noise
RAM	Advanced-Grade Composite, 12x142mm thru-axle, disc
GAFFEL	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	Liv Contact SL 31.8mm, 8-degree flare drop XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
GREPPAR	Liv Stratus Elite 2.0
STAM	Giant Contact SL AeroLight XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SADELSTOLPE	Giant Variant, composite, -5/+15mm offset
SADEL	Liv Alacra SL
DRIVLINJA	
VÄXLAR	SRAM Rival AXS
FRAMVÄXEL	SRAM Rival AXS
BAKVÄXEL	SRAM Rival AXS
BROMSAR	SRAM Rival eTap hydraulic, SRAM PaceLine rotors [F] 160mm, [R] 140mm
BROMSSPAKAR	SRAM Rival AXS
KASSETT	SRAM Rival, 12-speed, 10x36
KEDJA	SRAM Rival D1
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant SLR 1 40 WheelSystem, [F] 40mm, [R] 40mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
EKRAR	Sapim CX-Ray
DÄCK	Giant Gavia Course 0, tubeless, 700x25c (28mm), folding
EXTRAFUNKTIONER	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
GRÄNSER	
MAX DÄCKAVSTÅND	33mm

Price: 60 090,00 kr

GEOMETRY

RAM	XS	S	M	L
Längd sadelrör (mm)	420	450	480	510
Vinkel sadelrör	75,0°	74,5°	74,0°	73,5°
Topprörets längd (mm)	508	524	540	555
Styrhuvud Längd (mm)	120	135	155	175
Vinkel styrhuvud	71,0°	72,0°	72,5°	72,5°
Gaffelvinkel (mm)	49	49	49	49
Spår (mm)	68	61	58	58
Hjulbas (mm)	973	977	984	994
Kedjestagslängd (mm)	405	405	405	405
Nedre fäste Drop (mm)	72	69,5	69,5	69,5
Stack (mm)	517	532	553	572
Reach (mm)	370	377	382	386
Stå över höjden (mm)	707	736	763	783
Styrets bredd (mm)	360	380	400	420
Stamlängd (mm)	80	90	100	110
Vevlängd (mm)	165	170	170	172,5
Hjulstorlek	700C	700C	700C	700C

All specifications listed are subject to change without notice.