LANGMA ADVANCED PRO 1 (PRO COMPACT)



SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, L
FARVER	Fancy White/Chrome
RAMME	Advanced-grade Composite, 12x142mm thru-axle, disc
FORGAFFEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
BAGDÆMPER	N/A
KOMPONENTER	
STYR	Liv Contact SL, 31.8mm, 8-degree flare drop, XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
GREB / STYRBÅND	Liv Stratus Elite 2.0
FREMPIND	Giant Contact SL AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SADELPIND	Giant Variant, composite, -5/+15mm offset
SADEL	Liv Alacra SL
PEDALER	platform pedal [GCS,GTS], N/A [all other GSC]
GEARGRUPPE	
SKIFTEGREB	Shimano 105 Di2
FORSKIFTER	Shimano 105 Di2 FD-R7150
BAGSKIFTER	Shimano 105 Di2 FD-R7150
BREMSER	Shimano 105 Di2 hydraulic, Shimano RT-CL700 rotors, [F] 160mm, [R] 140mm
BREMSEGREB	Shimano 105 Di2
KASSETTE	Shimano 105, 12-speed, 11x34
KÆDE	KMC X12L-1
KRANKSÆT	Shimano 105, 36/52 with Giant Power Pro power meter XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
KRANKBOKS	Shimano, press fit

HJUL	
FÆLGE	Giant SLR 1 40 WheelSystem, [F] 40mm, [R] 40mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
EGER	Sapim CX-Ray
DÆK	Giant Gavia Course 0, tubeless, 700x25c (28mm), folding
EKSTRA	computer mount, tubeless prepared, 33mm max tire size
GRÆNSER	
MAX DÆKSTØRRELSE	33mm

Pris: 38.999,00 kr.

GEOMETRI

RAMME	XS	S	M	L
Sadelrørslængde (mm)	420	450	480	510
Sadelrørsvinkel	75,0°	74,5°	74,0°	73,5°
Overrørslængde (mm)	508	524	540	555
Kronrørslængde (mm)	120	135	155	175
Kronrøsvinkel	71,0°	72,0°	72,5°	72,5°
Forgaffel fremspring (rake) (mm)	49	49	49	49
Sti (mm)	68	61	58	58
Akselafstand (mm)	973	977	984	994
Kædestagslængde (mm)	405	405	405	405
Krankboks drop (mm)	72	70	70	70
Stack (mm)	517	532	553	572
Reach (mm)	370	377	382	386
Skridthøjde (mm)	707	736	763	783
Styrbredde (mm)	360	380	400	420
Frempindslængde (mm)	80	90	100	110
Pedalarmslængde (mm)	165	165	170	172,5

Alle de anførte specifikationer kan ændres uden varsel.