

LANGMA ADVANCED PRO DISC 0



SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Gloss Carbon Smoke / Sincity
FRAME	Advanced-Grade Composite, disc
FORK	Advanced-Grade Composite, full-composite OverDrive 2 steerer, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv Contact SLR XS:36cm, S:38cm, M:40cm
GRIPS	Liv All Condition
STEM	Giant Contact SL XS:80mm, S:90mm, M:100mm
SEATPOST	Giant Variant, composite XS:357mm, S:357mm, M:357mm
SADDLE	Liv Alacra SL CS
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	Shimano Ultegra Di2 ST-R8170 2x12
FRONT DERAILLEUR	Shimano Ultegra Di2 FD-R8150
REAR DERAILLEUR	Shimano Ultegra Di2 RD-R8150 max 34T
BRAKES	Shimano Ultegra Di2 hydraulic, Shimano RT-MT800 rotors [F]160mm, [R]140mm
BRAKE LEVERS	Shimano Ultegra Di2 hydraulic
CASSETTE	Shimano Ultegra, 12-speed, 11x30
CHAIN	Shimano Ultegra
CRANKSET	Shimano Ultegra, 36/52 XS:165mm, S:170mm, M:170mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 1 36 Disc Hookless WheelSystem (22mm inner rim width)
HUBS	Giant SLR 1 36 Disc WheelSystem, 12mm thru-axle
SPOKES	Giant SLR 1 36 Disc WheelSystem
TYRES	CADEX Race, tubeless, 700x25c (effective width 26.5mm), folding
EXTRAS	Computer mount, RideSense Bluetooth/ANT+, factory tubeless set up including sealant,
LIMITS	
MAX TYRE CLEARANCE	32mm

Price: £5,599.00

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	420	450	480
Seat Tube Angle	75.0°	74.5°	74.0°
Top Tube Length (mm)	508	524	540
Head Tube Length (mm)	120	135	155
Head Tube Angle	71.0°	72.0°	72.5°
Fork Rake (mm)	49	49	49
Trail (mm)	67.8	61.4	58.2
Wheelbase (mm)	973	977.2	984.2
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	72	69.5	69.5
Stack (mm)	516.5	531.8	552.6
Reach (mm)	369.6	376.5	381.5
Stand Over Height (mm)	700	730	760
Handlebar Width (mm)	360	380	400
Stem Length (mm)	80	90	100
Crank Length (mm)	165	170	170
Wheel Size	700C	700C	700C

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.