LANGMA ADVANCED SL 0



SPECS

ΣΚΕΛΕΤΌΣ	
ΜΕΓΈΘΗ	XXS, XS, S, M, L
ΧΡΏΜΑΤΑ	Raw Carbon/Rainbow Black/Iris
ΣΚΕΛΕΤΌΣ	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
ΠΙΡΟΎΝΙ	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ΑΝΆΡΤΗΣΗ	N/A
ΕΞΑΡΤΉΜΑΤΑ	
ΤΙΜΌΝΙ	Liv Contact SLR , 31.8mm, 8-degree flare drop, XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
GRIPS	Liv Stratus Elite 2.0
ΛΑΙΜΌΣ ΤΙΜΟΝΙΟΎ	Giant Contact SLR AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
ΛΑΙΜΌΣ ΣΈΛΛΑΣ	Liv Integrated Seatpost, -5/+15mm offset
ΣΈΛΛΑ	CADEX AMP
ΠΕΝΤΆΛ	platform pedal [GCS,GTS], N/A [all other GSC]
ΜΕΤΆΔΟΣΗ	
ΛΕΒΙΈ ΤΑΧΥΤΉΤΩΝ	SRAM RED AXS
ΝΤΕΡΑΓΙΈΡ ΕΜΠΡΌΣΘΙΟ	SRAM RED AXS
ΝΤΕΡΑΓΙΈΡ ΟΠΊΣΘΙΟ.	SRAM RED AXS
ΦΡΈΝΑ	SRAM RED eTap hydraulic, SRAM PaceLine X rotors, [F] 160mm, [R] 140mm
ΜΑΝΈΤΕΣ ΦΡΈΝΩΝ	SRAM RED AXS
CASETTE Ή ΕΛΕΎΘΕΡΟ	SRAM RED, 12-speed, 10x33
ΑΛΥΣΊΔΑ	SRAM RED E1
ΔΙΣΚΟΒΡΑΧΊΩΝΑΣ	SRAM RED AXS, 35/48 with power meter, XXS:160mm, XS:165mm, S:165mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB ceramic, press fit

WHEELS	
ΣΤΕΦΆΝΙΑ	CADEX Max 40 WheelSystem, [F] 40mm, [R] 40mm
ΚΈΝΤΡΑ	[F] CADEX R3 Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C48 Aero Hub, 48t ratchet driver, CenterLock, 12mm thru-axle
ΑΚΤΊΝΕΣ	CADEX Aero Carbon Spoke
ΕΛΑΣΤΙΚΆ	CADEX Road Race GC, tubeless, 700x28c, folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΌΣ	XXS	XS	S	M	L
Seat Tube Length (mm)	600	640	680	720	760
Seat Tube Angle	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	498	508	524	540	555
Head Tube Length (mm)	105	120	135	155	175
Head Tube Angle	70,0°	71,0°	72,0°	72,5°	72,5°
Fork Rake (mm)	49	49	49	49	49
Trail (mm)	74	68	61	58	58
Wheelbase (mm)	970	973	977	984	994
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	70
Stack (mm)	499	517	532	553	572
Reach (mm)	364	370	377	382	386
Stand Over Height (mm)	685	707	736	763	783
Handlebar Width (mm)	360	360	380	400	420
Stem Length (mm)	80	80	90	100	110
Crank Length (mm)	160	165	165	170	172,5

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση