LANGMA ADVANCED SL 0



SPECIFIKACIJE

OKVIR	
VELIČINE	XXS, XS, S, M, L
BOJE	Raw Carbon/Rainbow Black/Iris
OKVIR	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
VILICA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTIZER	N/A
KOMPONENTE	
VOLAN	Liv Contact SLR , 31.8mm, 8-degree flare drop, XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
GRIPS	Liv Stratus Elite 2.0
LULA VOLANA	Giant Contact SLR AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
CIJEV SJEDALA	Liv Integrated Seatpost, -5/+15mm offset
SJEDALO	CADEX AMP
PEDALE	platform pedal [GCS,GTS], N/A [all other GSC]
POGON	
RUČICE MJENJAČA	SRAM RED AXS
PREDNJI MJENJAČ	SRAM RED AXS
STRAŽNJI MJENJAČ	SRAM RED AXS
KOČNICE	SRAM RED eTap hydraulic, SRAM PaceLine X rotors, [F] 160mm, [R] 140mm
RUČICE KOČNICA	SRAM RED AXS
KAZETA	SRAM RED, 12-speed, 10x33
LANAC	SRAM RED E1
POGON	SRAM RED AXS, 35/48 with power meter, XXS:160mm, XS:165mm, S:165mm, M:170mm, L:172.5mm
OSOVINA POGONA (BB)	SRAM DUB ceramic, press fit

KOTAČI	
OBRUČI	CADEX Max 40 WheelSystem, [F] 40mm, [R] 40mm
NABE	[F] CADEX R3 Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C48 Aero Hub, 48t ratchet driver, CenterLock, 12mm thru-axle
ŽBICE	CADEX Aero Carbon Spoke
GUME	CADEX Road Race GC, tubeless, 700x28c, folding
DODACI	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRIJA

OKVIR	XXS	XS	S	M	L
Dužina cijevi sjedala (mm)	600	640	680	720	760
Kut cijevi sjedala	75,0°	75,0°	74,5°	74,0°	73,5°
Dužina gornje cijevi (mm)	498	508	524	540	555
Dužina prednje cijevi (mm)	105	120	135	155	175
Kut vilice	70,0°	71,0°	72,0°	72,5°	72,5°
Zakrivljenost vilice (offset) (mm)	49	49	49	49	49
Staza (mm)	74	68	61	58	58
Međuosovinski razmak kotača (mm)	970	973	977	984	994
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	405	405	405	405	405
Položaj osovine pogona (mm)	72	72	70	70	70
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	499	517	532	553	572
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	364	370	377	382	386
Prekoračna visina (mm)	685	707	736	763	783
Širina volana (mm)	360	360	380	400	420
Dužina lule volana (mm)	80	80	90	100	110
Dužina poluge pedale (mm)	160	165	165	170	172,5

Sve navedene specifikacije podložne su promjeni bez prethodne najave.