LANGMA ADVANCED SL 0



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XXS, XS, S, M, L
BARVE	Raw Carbon/Rainbow Black/Iris
OKVIR	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
VILICE	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Liv Contact SLR , 31.8mm, 8-degree flare drop, XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
GRIPS	Liv Stratus Elite 2.0
OPORA KRMILA	Giant Contact SLR AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
OPORA SEDEŽA	Liv Integrated Seatpost, -5/+15mm offset
SEDEŽ	CADEX AMP
PEDALA	platform pedal [GCS,GTS], N/A [all other GSC]
POGON	
PRESTAVNE ROČICE	SRAM RED AXS
PREDNJI MENJALNIK	SRAM RED AXS
ZADNJI MENJALNIK	SRAM RED AXS
ZAVORE	SRAM RED eTap hydraulic, SRAM PaceLine X rotors, [F] 160mm, [R] 140mm
ZAVORNE ROČICE	SRAM RED AXS
VERIŽNIK	SRAM RED, 12-speed, 10x33
VERIGA	SRAM RED E1
GONILKE Z VERIŽNIKI	SRAM RED AXS, 35/48 with power meter, XXS:160mm, XS:165mm, S:165mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB ceramic, press fit

OBROČNIKI	
OBROČI	CADEX Max 40 WheelSystem, [F] 40mm, [R] 40mm
PESTA	[F] CADEX R3 Hub, CenterLock, 12mm thru-axle, [R] CADEX R3-C48 Aero Hub, 48t ratchet driver, CenterLock, 12mm thru-axle
NAPERE	CADEX Aero Carbon Spoke
PLAŠČI	CADEX Road Race GC, tubeless, 700x28c, folding
DODATKI	computer mount, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRIJA

OKVIR	XXS	XS	S	M	L
Dolžina sedežne cevi (mm)	600	640	680	720	760
Kot sedežne cevi	75,0°	75,0°	74,5°	74,0°	73,5°
Top Tube Length (mm)	498	508	524	540	555
Višina glave okvirja (mm)	105	120	135	155	175
Krmilni kot	70,0°	71,0°	72,0°	72,5°	72,5°
Zamik vpetja osi (mm)	49	49	49	49	49
Trail (mm)	74	68	61	58	58
Medosna razdalja (mm)	970	973	977	984	994
Dolžina cevi ob verigi (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	72	72	70	70	70
Oddaljenost zgornje cevi od gonilne osi (mm)	499	517	532	553	572
Doseg (mm)	364	370	377	382	386
Višina zgornje cevi (mm)	685	707	736	763	783
Širina krmila (mm)	360	360	380	400	420
Dolžina opore krmila (mm)	80	80	90	100	110
Dolžina gonilke (mm)	160	165	165	170	172,5

Vse navedene specifikacije se lahko spremenijo brez obvestila.