

# LANGMA ADVANCED SL 0



## 產品規格

| 車架                   |  |
|----------------------|--|
| 尺寸                   | XXS, XS, S,  |
| 顏色                   | 珍珠藍綠   |
| 車架                   | Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc                   |
| 前叉                   | Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc |
| COMPONENTS           |  |
| 車把手                  | Liv Contact SLR 31.8mm, 8-degree flare drop XXS: 34/36cm, XS: 34/36cm, S: 36/38cm,           |
| 把手帶/套                | Liv Stratus Elite 2.0  |
| 聲桿                   | Giant Contact SLR AeroLight XXS: 80mm, XS: 80mm, S: 90mm,                                    |
| 座桿                   | Liv Integrated Seatpost, -5/+15mm offset   |
| 坐墊                   | CADEX AMP  |
| DRIVETRAIN           |  |
| 變速把手                 | SRAM RED AXS   |
| 前變速器                 | SRAM RED AXS   |
| 後變速器                 | SRAM RED AXS   |
| 煞車系統                 | SRAM RED eTap hydraulic, SRAM PaceLine X rotors [F] 160mm, [R] 140mm                         |
| 煞車把手                 | SRAM RED AXS   |
| 飛輪                   | SRAM RED, 12-speed, 10x33  |
| 鍊條                   | SRAM RED   |
| 大齒盤                  | SRAM RED AXS, 35/48 with power meter XXS:165mm, XS:165mm, S:170mm,                           |
| BOTTOM BRACKET (B B) | SRAM DUB   |

| 輪組                 |  |
|--------------------|--|
| 輪圈                 | CADEX Max 40 WheelSystem, [F] 40mm, [R] 40mm   |
| 花鼓                 | [F] CADEX R3 Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C48 Aero Hub, 48t ratchet driver, CenterLock, 12mm thru-axle |
| 輻條                 | CADEX Aero Carbon Spoke  |
| 外胎                 | CADEX Race GC, tubeless, 700x28c (28mm), folding   |
| 其他                 | computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size                          |
| LIMITS             |  |
| MAX TIRE CLEARANCE | 33mm   |

Price: NT\$338,000

## 車架幾何

| 車架           | XXS   | XS    | S     |
|--------------|-------|-------|-------|
| 座(立)管長 (mm)  | 600   | 640   | 680   |
| 座(立)管角度      | 75.0° | 75.0° | 74.5° |
| 上管長度 (mm)    | 498   | 508   | 524   |
| 頭管長度 (mm)    | 105   | 120   | 135   |
| 頭管角度         | 70.0° | 71.0° | 72.0° |
| 前叉 (mm)      | 49    | 49    | 49    |
| Trail (mm)   | 74    | 68    | 61    |
| 前後輪距 (mm)    | 970   | 973   | 977   |
| 後下叉長度 (mm)   | 405   | 405   | 405   |
| 五通下降高度 (mm)  | 72    | 72    | 69.5  |
| 頭碗至五通高度 (mm) | 499   | 517   | 532   |
| 頭碗至五通長度 (mm) | 364   | 370   | 377   |
| 上管至地面高度 (mm) | 685   | 707   | 736   |
| 把手寬 (mm)     | 360   | 360   | 380   |
| 龍頭長度 (mm)    | 80    | 80    | 90    |
| 曲柄長度 (mm)    | 165   | 165   | 170   |
| 輪組尺寸         | 700C  | 700C  | 700C  |

\* 捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。