

# LANGMA ADVANCED SL 1



## SPECS

| FRAME            |                                                                                                               |
|------------------|---------------------------------------------------------------------------------------------------------------|
| SIZES            | XXS, XS, S, M, L                                                                                              |
| COLOURS          | Cosmic Dust/Chrome                                                                                            |
| FRAME            | Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc                                    |
| FORK             | Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc                  |
| COMPONENTS       |                                                                                                               |
| HANDLEBAR        | Liv Contact SLR 31.8mm, 8-degree flare drop XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm     |
| GRIPS            | Liv Stratus Elite 2.0                                                                                         |
| STEM             | Giant Contact SLR AeroLight XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm                                  |
| SEATPOST         | Liv Integrated Seatpost, -5/+15mm offset                                                                      |
| SADDLE           | Liv Alacra SLR                                                                                                |
| DRIVETRAIN       |                                                                                                               |
| SHIFTERS         | Shimano Ultegra Di2                                                                                           |
| FRONT DERAILLEUR | Shimano Ultegra Di2 FD-R8150                                                                                  |
| REAR DERAILLEUR  | Shimano Ultegra Di2 RD-R8150                                                                                  |
| BRAKES           | Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm                                     |
| BRAKE LEVERS     | Shimano Ultegra Di2                                                                                           |
| CASSETTE         | Shimano Ultegra, 12-speed, 11x34                                                                              |
| CHAIN            | Shimano CN-M8100                                                                                              |
| CRANKSET         | Shimano Ultegra, 36/52 with Giant Power Pro power meter XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm |
| BOTTOM BRACKET   | Shimano, press fit                                                                                            |

| WHEELS             |                                                                                                                                   |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| RIMS               | Giant SLR 0 40 WheelSystem, [F] 40mm, [R] 40mm                                                                                    |
| HUBS               | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle |
| SPOKES             | Giant Aero Carbon Spoke                                                                                                           |
| TIRES              | CADEX Race GC, tubeless, 700x28c (28mm), folding                                                                                  |
| EXTRAS             | computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size                                     |
| LIMITS             |                                                                                                                                   |
| MAX TIRE CLEARANCE | 33mm                                                                                                                              |

**Suggested Retail Price (CDN): \$9,999.00**

## FRAME GEOMETRY

| FRAME                    | XS    | S     | M     |
|--------------------------|-------|-------|-------|
| Seat Tube Length (mm)    | 640   | 680   | 720   |
| Seat Tube Angle          | 75.0° | 74.5° | 74.0° |
| Top Tube Length (mm)     | 508   | 524   | 540   |
| Head Tube Length (mm)    | 120   | 135   | 155   |
| Head Tube Angle          | 71.0° | 72.0° | 72.5° |
| Fork Rake (mm)           | 49    | 49    | 49    |
| Trail (mm)               | 68    | 61    | 58    |
| Wheelbase (mm)           | 973   | 977   | 984   |
| Chain Stay Length (mm)   | 405   | 405   | 405   |
| Bottom Bracket Drop (mm) | 72    | 69.5  | 69.5  |
| Stack (mm)               | 517   | 532   | 553   |
| Reach (mm)               | 370   | 377   | 382   |
| Stand Over Height (mm)   | 707   | 736   | 763   |
| Handlebar Width (mm)     | 360   | 380   | 400   |
| Stem Length (mm)         | 80    | 90    | 100   |
| Crank Length (mm)        | 165   | 170   | 170   |
| Wheel Size               | 700C  | 700C  | 700C  |

*All prices and specifications are subject to change without notice.*