

LANGMA ADVANCED SL 1



TEKNISET TIEDOT

RUNKO	
KOOT	XXS, XS, S, M, L
VÄRIT	Cosmic Dust/Chrome
RUNKO	Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc
HAARUKKA	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTIT	
OHJAUSTANKO	Liv Contact SLR 31.8mm, 8-degree flare drop XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
GRIPIT	Liv Stratus Elite 2.0
OHJAINKANNATIN	Giant Contact SLR AeroLight XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
SATULATOLPPA	Liv Integrated Seatpost, -5/+15mm offset
SATULA	Liv Alacra SLR
VOIMANSIIRTO	
VAIHDEVIPU	Shimano Ultegra Di2
ETUVAIHTAJA	Shimano Ultegra Di2 FD-R8150
TAKAVAIHTAJA	Shimano Ultegra Di2 RD-R8150
JARRUT	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
JARRUKAHVAT	Shimano Ultegra Di2
RATASPAKKA	Shimano Ultegra, 12-speed, 11x34
KETJUT	Shimano CN-M8100
KAMPISARJA	Shimano Ultegra, 36/52 with Giant Power Pro power meter XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
KESKIÖ	Shimano, press fit

RENKAAT	
VANTEET	Giant SLR 0 40 WheelSystem, [F] 40mm, [R] 40mm
NAVAT	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
PINNAT	Giant Aero Carbon Spoke
RENKAAT	CADEX Race GC, tubeless, 700x28c (28mm), folding
LISÄTIEDOT	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
RAJOITTEET	
MAX RENGASVARA	33mm

Suositus hinta: 8 709,00 €

GEOMETRIA

RUNKO	XS	S	M	L
Satulaputken pituus (mm)	640	680	720	760
Satulaputken kulma	75,0°	74,5°	74,0°	73,5°
Vaakaputken pituus (mm)	508	524	540	555
Emäputken pituus (mm)	120	135	155	175
Emäputken kulma	71,0°	72,0°	72,5°	72,5°
Haarukan offset (mm)	49	49	49	49
Trail-mitta (mm)	68	61	58	58
Akseliväli (mm)	973	977	984	994
Takahaarukan alaputken pituus (mm)	405	405	405	405
Keskiön pudotus (mm)	72	69,5	69,5	69,5
Stack-mitta (mm)	517	532	553	572
Reach-mitta (mm)	370	377	382	386
Standover-mitta (mm)	707	736	763	783
Ohjaustangon leveys (mm)	360	380	400	420
Ohjainkannattimen pituus (mm)	80	90	100	110
Kammen pituus (mm)	165	170	170	172,5
Rengaskoko	700C	700C	700C	700C

Kaikki ilmoitettut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.