

LANGMA ADVANCED SL 1



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Cosmic Dust/Chrome
FRAME	Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc
VOORVORK	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
ONDERDELEN	
STUUR	Liv Contact SLR 31.8mm, 8-degree flare drop XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
HANDVATTEN	Liv Stratus Elite 2.0
STUURPEN	Giant Contact SLR AeroLight XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
ZADELPEN	Liv Integrated Seatpost, -5/+15mm offset
ZADEL	Liv Alacra SLR
AFMONTAGE	
SHIFTERS	Shimano Ultegra Di2
VOORDERAILLEUR	Shimano Ultegra Di2 FD-R8150
ACHTERDERAILLEUR	Shimano Ultegra Di2 RD-R8150
REMMEN	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
REMHENDELS	Shimano Ultegra Di2
CASSETTE	Shimano Ultegra, 12-speed, 11x34
AANDRIJVING	Shimano CN-M8100
CRANKSET	Shimano Ultegra, 36/52 with Giant Power Pro power meter XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant SLR 0 40 WheelSystem, [F] 40mm, [R] 40mm
NAVEN	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	Giant Aero Carbon Spoke
BANDEN	CADEX Race GC, tubeless, 700x28c (28mm), folding
EXTRA'S	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
LIMITS	
MAXIMALE BANDENVRIJHEID	33mm

Adviesprijs: € 8.399,00

GEOMETRIE

FRAME	XS	S	M	L
Zitbuis Lengte (mm)	640	680	720	760
Zitbuis Hoek	75,0°	74,5°	74,0°	73,5°
Frame Lengte (horizontaal) (mm)	508	524	540	555
Balhoofdbuis Lengte (mm)	120	135	155	175
Balhoofdbuis Hoek	71,0°	72,0°	72,5°	72,5°
Vork Sprong (mm)	49	49	49	49
Naloop (mm)	68	61	58	58
Wielbasis (mm)	973	977	984	994
Liggende achtervork lengte (mm)	405	405	405	405
Bottom Bracket Drop (mm)	72	69,5	69,5	69,5
Stack (mm)	517	532	553	572
Reach (mm)	370	377	382	386
Stand Over Height (mm)	707	736	763	783
Stuur breedte (mm)	360	380	400	420
Stuurpen Lengte (mm)	80	90	100	110
Cranklengte (mm)	165	170	170	172,5
Wielmaat	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.