LANGMA ADVANCED SL 1



SPECIFIKACIJE

OKVIR	
VELIČINE	XXS, XS, S, M, L
BOJE	Cosmic Dust/Chrome
OKVIR	Advanced SL-Grade Composite, 12x142mm thru-axle, integrated seatpost, disc
VILICA	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTE	
VOLAN	Liv Contact SLR 31.8mm, 8-degree flare drop XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
GRIPS	Liv Stratus Elite 2.0
LULA VOLANA	Giant Contact SLR AeroLight XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
CIJEV SJEDALA	Liv Integrated Seatpost, -5/+15mm offset
SJEDALO	Liv Alacra SLR
POGON	
RUČICE MJENJAČA	Shimano Ultegra Di2
PREDNJI MJENJAČ	Shimano Ultegra Di2 FD-R8150
STRAŽNJI MJENJAČ	Shimano Ultegra Di2 RD-R8150
KOČNICE	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]140mm
RUČICE KOČNICA	Shimano Ultegra Di2
KAZETA	Shimano Ultegra, 12-speed, 11x34
LANAC	Shimano CN-M8100
POGON	Shimano Ultegra, 36/52 with Giant Power Pro power meter XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
OSOVINA POGONA (BB)	Shimano, press fit

KOTAČI	
OBRUČI	Giant SLR 0 40 WheelSystem, [F] 40mm, [R] 40mm
NABE	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
ŽBICE	Giant Aero Carbon Spoke
GUME	CADEX Race GC, tubeless, 700x28c (28mm), folding
DODACI	computer mount, Airway Eco Composite water bottle cage, tubeless prepared, 33mm max tire size
LIMITS	
MAX TIRE CLEARANCE	33mm

GEOMETRIJA

OKVIR	XXS	XS	S	M	L
Dužina cijevi sjedala (mm)	600	640	680	720	760
Kut cijevi sjedala	75,0°	75,0°	74,5°	74,0°	73,5°
Dužina gornje cijevi (mm)	498	508	524	540	555
Dužina prednje cijevi (mm)	105	120	135	155	175
Kut vilice	70,0°	71,0°	72,0°	72,5°	72,5°
Zakrivljenost vilice (offset) (mm)	49	49	49	49	49
Staza (mm)	74	68	61	58	58
Međuosovinski razmak kotača (mm)	970	973	977	984	994
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	405	405	405	405	405
Položaj osovine pogona (mm)	72	72	69,5	69,5	69,5
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	499	517	532	553	572
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	364	370	377	382	386
Prekoračna visina (mm)	685	707	736	763	783
Širina volana (mm)	360	360	380	400	420
Dužina lule volana (mm)	80	80	90	100	110
Dužina poluge pedale (mm)	165	165	170	170	172,5
Veličina kotača	700C	700C	700C	700C	700C

Sve navedene specifikacije podložne su promjeni bez prethodne najave.