LANGMA ADVANCED SL 1



SPECS

QUADRO	
TAMANHOS	XXS, XS, S, M, L
CORES	Dreamy Blue/Chrome
QUADRO	Advanced SL-grade Composite, 12x142mm thru-axle, integrated seatpost, disc
FORQUILHA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTECEDORES	N/A
COMPONENTES	
GUIADOR	Liv Contact SLR , 31.8mm, 8-degree flare drop, XXS: 34/36cm, XS: 34/36cm, S: 36/38cm, M: 38/40cm, L: 39/42cm
PUNHOS	Liv Stratus Elite 2.0
AVANÇO	Giant Contact SLR AeroLight, XXS: 80mm, XS: 80mm, S: 90mm, M: 100mm, L: 110mm
ESPIGÃO DE SELIM	Liv Integrated Seatpost, -5/+15mm offset
SELIM	Liv Alacra SLR
PEDAIS	platform pedal [GCS,GTS], N/A [all other GSC]
TRANSMISSÃO	
MANETES	Shimano Ultegra Di2
DESVIADOR DIANTEIRO	Shimano Ultegra Di2 FD-R8150
DESVIADOR TRASEIRO	Shimano Ultegra Di2 RD-R8150
TRAVÕES	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors, [F]160mm, [R]140mm
MANÍPULOS DOS TRAVÕES	Shimano Ultegra Di2
CASSETE	Shimano Ultegra, 12-speed, 11x34
CORRENTE	Shimano CN-M8100
CONJUNTO PEDALEIRO	Shimano Ultegra, 36/52 with Giant Power Pro power meter, XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
MOVIMENTO CENTRAL	Shimano, press fit

RODAS	
AROS	Giant SLR 0 40 WheelSystem, [F] 40mm, [R] 40mm
CUBOS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 40T ratchet driver, CenterLock, 12mm thru-axle
RAIOS	Giant Aero Carbon Spoke
PNEUS	CADEX Road Race GC, tubeless, 700x28c, folding
EXTRAS	computer mount, tubeless prepared, 33mm max tire size
LIMITES	
FOLGA MÁXIMA DO PNEU	33mm

Preço: 7 299,00 €

GEOMETRIA

QUADRO	XS	S
Comprimento do tubo do assento (mm)	640	680
Ângulo do tubo do assento	75,0°	74,5°
Comprimento do tubo superior (mm)	508	524
Comprimento do tubo principal (mm)	120	135
Ângulo do tubo principal	71,0°	72,0°
Garfo ancinho (mm)	49	49
Trilha (mm)	68	61
distância entre eixos (mm)	973	977
Comprimento Chain Stay (mm)	405	405
Suporte inferior (mm)	72	70
Pilha (mm)	517	532
Alcançar (mm)	370	377
Altura do standover (mm)	707	736
Largura do guidão (mm)	360	380
Comprimento da haste (mm)	80	90
Comprimento da Manivela (mm)	165	165

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.