

# LURRA 1



## SPECS

FRAME	
<b>SIZES</b>	XS (27.5"), S (27.5"), S (29"), M (29"), L (29")
<b>COLORS</b>	Starry Night (matte)
<b>FRAME</b>	ALUXX SL-Grade Aluminum, 12x148 thru-axle
<b>FORK</b>	Giant Crest 34 SL RCL, 130mm, 15x110
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact TR35, alloy, 27.5": XS: 760mm, S: 760mm 29": S: 760mm, M: 760mm, L: 780mm
<b>GRIPS</b>	Liv Sole-O
<b>STEM</b>	Giant Contact SL 35 For 27.5": XS: 40mm, S: 40mm For 29": S: 40mm, M: 50mm, L: 50mm
<b>SEATPOST</b>	Giant Contact Switch dropper, remote For 27.5": XS: 100mm travel / 30.9 x 345mm S: 100mm travel / 30.9 x 345mm For 29": S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 440mm
<b>SADDLE</b>	Liv Sylvia
<b>PEDALS</b>	platform
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM SX Eagle, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	SRAM NX Eagle
<b>BRAKES</b>	Shimano BR-MT420 [F], Shimano BR-MT410 [R], hydraulic, Shimano SM-RT26 rotors [F]180mm, [R]180mm
<b>BRAKE LEVERS</b>	Shimano BL-MT401
<b>CASSETTE</b>	SRAM SX Eagle, 11x50
<b>CHAIN</b>	SRAM SX Eagle
<b>CRANKSET</b>	*SRAM SX Eagle PowerSpline, 30t, For 27.5": XS: 165mm, S: 170mm For 29": S: 170mm, M: 170mm, L: 170mm
<b>BOTTOM BRACKET</b>	SRAM PowerSpline, threaded

WHEELS	
<b>RIMS</b>	For 27.5": Giant AM 27.5, tubeless ready, sleeve-joint rim, 30mm inner width For 29": Giant AM 29, tubeless ready, sleeve-joint rim, 30mm inner width
<b>HUBS</b>	alloy, open-race sealed bearings
<b>SPOKES</b>	Sapim
<b>TIRES</b>	For 27.5": Maxxis Ardent Race 27.5x2.6, EXO, TR, tubeless For 29": [F] Maxxis Minion DHF 29x2.5 WT, EXO, TR, tubeless, [R] Maxxis Aggressor 29x2.5 WT, EXO, TR, tubeless
<b>EXTRAS</b>	For 27.5": tubeless prepared, max tire size 2.6", max chainring size 32t For 29": tubeless prepared, max tire size 2.5", max chainring size 32t

**Recommended Retail Price: \$1,650.00**

## GEOMETRY

FRAME	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")
Seat Tube Length (inch)	14.2	15	15	16.1	16.9
Seat Tube Angle	76.0°	76.0°	76.5°	76.5°	76.5°
Top Tube Length (inch)	21.4	22.2	21.8	22.6	23.5
Head Tube Length (inch)	3.7	4.1	3.5	3.9	4.3
Head Tube Angle	66.0°	66.0°	66.0°	66.0°	66.0°
Fork Rake (inch)	1.7	1.7	1.7	1.7	1.7
Trail (inch)	4.4	4.4	4.8	4.8	4.8
Wheelbase (inch)	44	44.9	44.7	45.6	46.5
Chain Stay Length (inch)	17.2	17.2	17.2	17.2	17.2
Bottom Bracket Drop (inch)	2.4	2.4	2.4	2.4	2.4
Stack (inch)	23.9	24.3	24.3	24.7	25
Reach (inch)	15.5	16.1	16	16.7	17.4
Stand Over Height (inch)	24.1	26	26	28	29
Handlebar Width (inch)	29.9	29.9	29.9	29.9	30.7
Stem Length (inch)	1.6	1.6	1.6	2	2
Crank Length (inch)	6.5	6.7	6.7	6.7	6.7
Wheel Size	27.5"	27.5"	29"	29"	29"

*\*All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*