



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS (27.5"), S (27.5"), S (29"), M (29"), L (29")
BARVE	Starry Night
OKVIR	ALUXX SL-Grade Aluminum, 12x148 thru-axle
VILICE	Giant Crest 34 SL RCL, 130mm, 15x110
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Contact TR35, alloy, 27.5": XS: 760mm, S: 760mm 29": S: 760mm, M: 760mm, L: 780mm
GRIPS	Liv Sole-O
OPORA KRMILA	Giant Contact SL 35 For 27.5": XS: 40mm, S: 40mm For 29": S: 40mm, M: 50mm, L: 50mm
OPORA SEDEŽA	Giant Contact Switch dropper, remote For 27.5": XS: 100mm travel / 30.9 x 345mm S: 100mm travel / 30.9 x 345mm For 29": S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 440mm
SEDEŽ	Liv Sylvia
PEDALA	platform
POGON	
PRESTAVNE ROČICE	SRAM SX Eagle, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM NX Eagle
ZAVORE	Shimano BR-MT420 [F], Shimano BR-MT410 [R], hydraulic, Shimano SM-RT26 rotors [F]180mm, [R]180mm
ZAVORNE ROČICE	Shimano BL-MT401
VERIŽNIK	SRAM SX Eagle, 11x50
VERIGA	SRAM SX Eagle
GONILKE Z VERIŽNIKI	"SRAM SX Eagle PowerSpline, 30t, For 27.5": XS: 165mm, S: 170mm For 29": S: 170mm, M: 170mm, L: 170mm
BOTTOM BRACKET	SRAM PowerSpline, threaded

OBROČNIKI

OBROČI	For 27.5": Giant AM 27.5, tubeless ready, sleeve-joint rim, 30mm inner width For 29": Giant AM 29, tubeless ready, sleeve-joint rim, 30mm inner width
PESTA	alloy, sealed
NAPERE	Sapim
PLAŠČI	For 27.5": Maxxis Ardent Race 27.5x2.6, EXO, TR, tubeless For 29": [F] Maxxis Minion DHF 29x2.5 WT, EXO, TR, tubeless, [R] Maxxis Aggressor 29x2.5 WT, EXO, TR, tubeless
DODATKI	For 27.5": tubeless prepared, max tire size 2.6", max chainring size 32t For 29": tubeless prepared, max tire size 2.5", max chainring size 32t

GEOMETRIJA

OKVIR	XS (27.5")	S (27.5")	S (29")	M (29")	L (29")
Dolžina sedežne cevi (mm)	360	380	380	410	430
Kot sedežne cevi	76,0°	76,0°	76,5°	76,5°	76,5°
Top Tube Length (mm)	544	564	554	575	596
Višina glave okvirja (mm)	95	105	90	100	110
Krmlini kot	66,0°	66,0°	66,0°	66,0°	66,0°
Zamik vpetja osi (mm)	44	44	44	44	44
Trail (mm)	113,9	113,9	121,7	121,7	121,7
Medosna razdalja (mm)	1118	1140	1136	1159	1182
Dolžina cevi ob verigi (mm)	438	438	438	438	438
Bottom Bracket Drop (mm)	60	60	60	60	60
Oddaljenost zgornje cevi od gonilne osi (mm)	608	617	618	627	636
Doseg (mm)	393	410	406	425	443
Višina zgornje cevi (mm)	613	661	661	712	737
Širina krmila (mm)	760	760	760	760	780
Dolžina opore krmila (mm)	40	40	40	50	50
Dolžina gonilke (mm)	165	170	170	170	170
Velikost obročnikov	27.5"	27.5"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.