

LURRA E+ 2



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport2, 75Nm, powered by Yamaha, PedalPlus 6-sensor technology
BEDIENINGSUNIT	Giant RideControl Dash, Smart Assist automatic mode, 5 support levels, USB-C (10W)
DISPLAY	Giant RideControl Dash, high-angle visibility, full color LCD display
ACCU	Giant EnergyPak 625Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 250 range extender compatible (exclude XS size)
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
MATEN	XS, S, M, L, (XS-S: 27.5 / M-L: 29)
FRAME	ALUXX SL aluminum, Overdrive 1.5" - 1.8" head tube, 148x12mm thru-axle, integrated KSA40 kickstand mount, EnergyPak Plus range extender compatible
VOORVORK	SR Suntour XCR 34 Boost 2-CR Coil 29 [XS-S], 27.5 [M-L], 130mm travel, Tapered 1.125"-1.5" steerer, 15LH-110
DEMPER	n/a
ONDERDELEN	
STUUR	Connect TR Riser 31.8 alloy 690mm [XS-S], 750mm [M-L]
HANDVATTEN	Liv Tactal Pro Single Lock-On
STUURPEN	Contact 31.8 alloy
ZADEL	Contact Switch Adj, adjustable dropper 30,9mm
ZADEL	Liv Ergo Contact Trail
PEDALEN	Aluminum Platform
AFMONTAGE	
SHIFTERS	Shimano Cues LinkGlide
VOORDERAILLEUR	n/a
ACHTERDERAILLEUR	Shimano Cues LinkGlide, 9-speed
REMMEN	Tektro HD-M285, hydraulic disc, 180mm
REMHENDELS	Tektro HD-M285
CASSETTE	Shimano Cues, LinkGlide, CS-LG300-9, 11-46T, 9-speed
AANDRIJVING	KMC eGlide NP/BK, e-bike optimized
CRANKSET	FSA MegaTooth direct-mount 1X steel 36T FSA Comet E-Bike crank arm
BOTTOM BRACKET	n/a

WIELSET	
VELGEN	XCT 27.5" [XS-S] / 29" [M-L] Tubeless Ready 25mm e-bike optimized
NAVEN	eTracker Boost 15x110 [F], 12x148mm [R]
SPAKEN	Stainless steel
BANDEN	Maxxis Rekon 27.5 x 2.4" [XS-S] / 29 x 2.4" [M-L], Fodable EXO 60TPI Tubeless
EXTRA'S	-
ACCESSOIRES	
VERLICHTING	-
SLOT	-
DRAGER	-

Adviesprijs: € 3.599,00

GEOMETRIE

FRAME	XS	S	M	L
Zitbuis Lengte (mm)	365	405	468	485
Seat Post Insertion Depth (mm)	200	240	280	320
Zitbuis Hoek	74,0°	74,0°	74,0°	74,0°
Frame Lengte (horizontaal) (mm)	550	570	590	610
Balhoofdbuis Lengte (mm)	110	120	120	140
Balhoofdbuis Hoek	66,0°	66,0°	66,0°	66,0°
Vork Sprong (mm)	44	44	51	51
Naloop (mm)	112	112	113	113
Wielbasis (mm)	1122	1143	1187	1210
Liggende achtersvork lengte (mm)	450	450	470	470
Bottom Bracket Drop (mm)	50	50	65	65
Stack (mm)	622	631	660	679
Reach (mm)	371	389	400	415
Stand Over Height (mm)	687	702	743	742
Stuur breedte (mm)	690	690	750	750
Stuurpen Lengte (mm)	40	40	50	60
Cranklengte (mm)	165	165	165	165
Wielmaat	[F] 27.5+"	[F] 27.5+"	[F] 29" [R]	[F] 29" [R]

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.