LURRA E+ EX



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 2, 85Nm PedalPlus 6-Sensor technology
CONTROLLER	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, high-angle visibility, full color LCD display
BATTERY	Giant EnergyPak Smart 750Wh
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	XS, S, M, L (XS-S: 27.5, M-L: 29er)
COLORS	Cray Dawn
FRAME	ALUXX aluminum, Overdrive 1.125" - 1.8" head tube, 148x12mm Thru-axle, integrated KSA40 kickstand mount
FORK	SR Suntour XCR34 2CR coil boost 130mm travel 15x110mm AH axle
COMPONENTS	
HANDLEBAR	Connect TR Riser 31.8 alloy 690mm [XS-S], 750mm [M-L]
GRIPS	Liv Tactal Pro Single Lock-On
STEM	Contact 31.8 alloy
SEATPOST	Contact Switch Core dropper seatpost, 100mm travel
SADDLE	Liv Ergo Contact Trail, ESG
PEDALS	Aluminum Platform
DRIVETRAIN	
SHIFTERS	Shimano Cues
REAR DERAILLEUR	Shimano Cues 10-speed
BRAKES	Shimano MT200, hydraulic disc,180mm [F/R]
BRAKE LEVERS	Shimano BL-MT200
CASSETTE	Shimano Cues11-48T 10-speed
CHAIN	Shimano Linkglide CN-LG500
CRANKSET	Forged allumin direct-mount chainring steel 36T, Forged alumium crank arms

WHEELS	
RIMS	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
HUBS	eTracker boost alloy 6-bolt disc 15x110mm[F] 12x148mm[R]
SPOKES	Stainless steel
TIRES	Maxxis Rekon 29x2.4", EXO, 60TPI
ACCESSORIES	
LIGHTING	Recon E HL50 [F] Axa BlueLine Steady E6 [R]
LOCK	ABUS Xplus battery lock
CARRIER	Rack-It MIK

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	365	405	468	485
Seat Tube Angle	74,0°	74,0°	74,0°	74,0°
Top Tube Length (mm)	550	570	590	610
Head Tube Length (mm)	110	120	120	140
Head Tube Angle	66,0°	66,0°	66,0°	66,0°
Fork Rake (mm)	44	44	51	51
Wheelbase (mm)	1122	1143	1187	1210
Chain Stay Length (mm)	450	450	470	470
Bottom Bracket Drop (mm)	50	50	65	65
Stack (mm)	622	631	660	679
Reach (mm)	371	389	400	415
Handlebar Width (mm)	690	690	750	750
Stem Length (mm)	40	40	50	60
Wheel Size	27.5+	27.5+	29"	29"

All specifications listed are subject to change without notice.