

PIQUE ADVANCED 29 0



SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S, M, L
BOJE	Mulberry Glitter/Black/Chrome
OKVIR	Advanced-grade composite front and rear triangles, 115mm FlexPoint Pro Suspension
VILICA	Fox 34 Float SC Factory, 120mm, FIT4 damper, Boost 15x110 Kabolt, tapered, tapered, 44mm offset, 3 position remote lockout
AMORTIZER	Fox Float SL Factory 165x45, custom tuned for Liv
KOMPONENTE	
VOLAN	Giant Contact SLR XC, composite, 35mm XS: 760mm, S: 760mm, M: 760mm, L: 760mm
GRIPS	Liv XC Pro, 32mm
LULA VOLANA	Giant Contact SL XC, alloy, 35mm XS: 60mm, S: 60mm, M: 70mm, L: 70mm
CIJEV SJEDALA	Fox Transfer dropper, remote XS: 100mm travel / 30.9 x 345mm S: 125mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 400mm L: 125mm travel / 30.9 x 400mm
SJEDALO	Fi'zi:k Vento Argo R5
PEDALE	platform
POGON	
RUČICE MJENJAČA	SRAM AXS, 1x12
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	SRAM XX Eagle, T-Type AXS
KOČNICE	Shimano XTR, hydraulic, Shimano RT-64 centerlock rotors [F]180mm, [R]160mm
RUČICE KOČNICA	Shimano XTR BL-M9100
KAZETA	SRAM XX CS 1299 SL T-Type, 10x52
LANAC	SRAM XX T-Type
POGON	SRAM XX SL T-Type, power meter, alloy chainring 32t, 55mm chainline XS:165mm, S:170mm, M:170mm, L:175mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	ZIPP 1ZERO HiTop SL 29 WheelSystem, 30mm inner width
NABE	XD, Centerlock
ŽBICE	Sapim
GUME	Maxxis Aspen, 29x2.4, foldable, TLR, EXO, tubeless
DODACI	tubeless prepared, custom Giant MRP chain guide, 3M clear foil down tube protector, max tire size 2.4-inch, max chainring size 34t. *Not compatible with 2023 or earlier RockShox Sid rear shocks.

GEOMETRIJA

OKVIR	XS	S	M	L
Dužina cijevi sjedala (mm)	380	410	440	470
Seat Post Insertion Depth (mm)	203	233	263	293
Kut cijevi sjedala	76,0°	76,0°	76,0°	76,0°
Dužina gornje cijevi (mm)	555	570	585	600
Dužina prednje cijevi (mm)	90	95	105	115
Kut vilice	67,0°	67,0°	67,0°	67,0°
Zakrivljenost vilice (offset) (mm)	44	44	44	44
Staza (mm)	112,2	112,2	112,2	112,2
Međuosovinski razmak kotača (mm)	1121	1137	1154	1170
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	435	435	435	435
Položaj osovine pogona (mm)	45	45	45	45
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	599	603	612	622
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	406	420	432	445
Prekoračna visina (mm)	748	767	770	791
Širina volana (mm)	760	760	760	760
Dužina lule volana (mm)	60	60	70	70
Dužina poluge pedale (mm)	165	170	170	175
Veličina kotača	29"	29"	29"	29"

Sve navedene specifikacije podložne su promjeni bez prethodne najave.