

# PIQUE ADVANCED 29 0



## SPECS

| FRAME            |                                                                                                                                                           |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| SIZES            | XS, S, M, L                                                                                                                                               |
| COLORS           | Mulberry Glitter/Black/Chrome                                                                                                                             |
| FRAME            | Advanced-grade composite front and rear triangles, 115mm FlexPoint Pro Suspension                                                                         |
| FORK             | Fox 34 Float SC Factory, 120mm, FIT4 damper, Boost 15x110 Kabolt, tapered, tapered, 44mm offset, 3 position remote lockout                                |
| SHOCK            | Fox Float SL Factory 165x45, custom tuned for Liv                                                                                                         |
| COMPONENTS       |                                                                                                                                                           |
| HANDLEBAR        | Giant Contact SLR XC, composite, 35mm XS: 760mm, S: 760mm, M: 760mm, L: 760mm                                                                             |
| GRIPS            | Liv XC Pro, 32mm                                                                                                                                          |
| STEM             | Giant Contact SL XC, alloy, 35mm XS: 60mm, S: 60mm, M: 70mm, L: 70mm                                                                                      |
| SEATPOST         | Fox Transfer dropper, remote XS: 100mm travel / 30.9 x 345mm S: 125mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 400mm L: 125mm travel / 30.9 x 400mm |
| SADDLE           | Fi'zi:k Vento Argo R5                                                                                                                                     |
| PEDALS           | platform                                                                                                                                                  |
| DRIVETRAIN       |                                                                                                                                                           |
| SHIFTERS         | SRAM AXS, 1x12                                                                                                                                            |
| FRONT DERAILLEUR | N/A                                                                                                                                                       |
| REAR DERAILLEUR  | SRAM XX Eagle, T-Type AXS                                                                                                                                 |
| BRAKES           | Shimano XTR, hydraulic, Shimano RT-64 centerlock rotors [F]180mm, [R]160mm                                                                                |
| BRAKE LEVERS     | Shimano XTR BL-M9100                                                                                                                                      |
| CASSETTE         | SRAM XX CS 1299 SL T-Type, 10x52                                                                                                                          |
| CHAIN            | SRAM XX T-Type                                                                                                                                            |
| CRANKSET         | SRAM XX SL T-Type, power meter, alloy chainring 32t, 55mm chainline XS:165mm, S:170mm, M:170mm, L:175mm                                                   |
| BOTTOM BRACKET   | SRAM DUB, press fit                                                                                                                                       |

| WHEELS |                                                                                                                                                                                                    |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RIMS   | ZIPP 1ZERO HiTop SL 29 WheelSystem, 30mm inner width                                                                                                                                               |
| HUBS   | XD, Centerlock                                                                                                                                                                                     |
| SPOKES | Sapim                                                                                                                                                                                              |
| TIRES  | Maxxis Aspen, 29x2.4, foldable, TLR, EXO, tubeless                                                                                                                                                 |
| EXTRAS | tubeless prepared, custom Giant MRP chain guide, 3M clear foil down tube protector, max tire size 2.4-inch, max chainring size 34t. *Not compatible with 2023 or earlier RockShox Sid rear shocks. |

## GEOMETRY

| FRAME                          | XS    | S     | M     | L     |
|--------------------------------|-------|-------|-------|-------|
| Seat Tube Length (mm)          | 380   | 410   | 440   | 470   |
| Seat Post Insertion Depth (mm) | 203   | 233   | 263   | 293   |
| Seat Tube Angle                | 76,0° | 76,0° | 76,0° | 76,0° |
| Top Tube Length (mm)           | 555   | 570   | 585   | 600   |
| Head Tube Length (mm)          | 90    | 95    | 105   | 115   |
| Head Tube Angle                | 67,0° | 67,0° | 67,0° | 67,0° |
| Fork Rake (mm)                 | 44    | 44    | 44    | 44    |
| Trail (mm)                     | 112,2 | 112,2 | 112,2 | 112,2 |
| Wheelbase (mm)                 | 1121  | 1137  | 1154  | 1170  |
| Chain Stay Length (mm)         | 435   | 435   | 435   | 435   |
| Bottom Bracket Drop (mm)       | 45    | 45    | 45    | 45    |
| Stack (mm)                     | 599   | 603   | 612   | 622   |
| Reach (mm)                     | 406   | 420   | 432   | 445   |
| Stand Over Height (mm)         | 748   | 767   | 770   | 791   |
| Handlebar Width (mm)           | 760   | 760   | 760   | 760   |
| Stem Length (mm)               | 60    | 60    | 70    | 70    |
| Crank Length (mm)              | 165   | 170   | 170   | 175   |
| Wheel Size                     | 29"   | 29"   | 29"   | 29"   |

All specifications listed are subject to change without notice.