PIQUE ADVANCED 29 0



SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Mulberry Glitter/Black/Chrome
FRAME	Advanced-grade composite front and rear triangles, 115mm FlexPoint Pro Suspension
FORK	Fox 34 Float SC Factory, 120mm, FIT4 damper, Boost 15x110 Kabolt, tapered, tapered, 44mm offset, 3 position remote lockout
SHOCK	Fox Float SL Factory 165x45, custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact SLR XC, composite, 35mm XS: 760mm, S: 760mm, M: 760mm, L: 760mm
GRIPS	Liv XC Pro, 32mm
STEM	Giant Contact SL XC, alloy, 35mm XS: 60mm, S: 60mm, M: 70mm, L: 70mm
SEATPOST	Fox Transfer dropper, remote XS: 100mm travel / 30.9 x 345mm S: 125mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 400mm L: 125mm travel / 30.9 x 400mm
SADDLE	Fi'zi:k Vento Argo R5
PEDALS	platform
DRIVETRAIN	
SHIFTERS	SRAM AXS, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM XX Eagle, T-Type AXS
BRAKES	Shimano XTR, hydraulic, Shimano RT-64 centerlock rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano XTR BL-M9100
CASSETTE	SRAM XX CS 1299 SL T-Type, 10x52
CHAIN	SRAM XX T-Type
CRANKSET	SRAM XX SL T-Type, power meter, alloy chainring 32t, 55mm chainline XS:165mm, S:170mm, M:170mm, L:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	ZIPP 1ZERO HiTop SL 29 WheelSystem, 30mm inner width
HUBS	XD, Centerlock
SPOKES	Sapim
TIRES	Maxxis Aspen, 29x2.4, foldable, TLR, EXO, tubeless
EXTRAS	tubeless prepared, custom Giant MRP chain guide, 3M clear foil down tube protector, max tire size 2.4-inch, max chainring size 34t. *Not compatible with 2023 or earlier RockShox Sid rear shocks.

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	380	410	440	470
Seat Post Insertion Depth (mm)	203	233	263	293
Seat Tube Angle	76,0°	76,0°	76,0°	76,0°
Top Tube Length (mm)	555	570	585	600
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	67,0°	67,0°	67,0°	67,0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	112,2	112,2	112,2	112,2
Wheelbase (mm)	1121	1137	1154	1170
Chain Stay Length (mm)	435	435	435	435
Bottom Bracket Drop (mm)	45	45	45	45
Stack (mm)	599	603	612	622
Reach (mm)	406	420	432	445
Stand Over Height (mm)	748	767	770	791
Handlebar Width (mm)	760	760	760	760
Stem Length (mm)	60	60	70	70
Crank Length (mm)	165	170	170	175
Wheel Size	29"	29"	29"	29"

All specifications listed are subject to change without notice.