



PIQUE ADVANCED 29 1



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Gloss Raw Carbon/Matte Raw Carbon/Chrome
FRAME	Advanced-grade composite front and rear triangles, 115mm FlexPoint Pro Suspension
FORK	Fox 34 Float SC Performance Elite, 120mm, FIT4 damper, Boost 15x110 KaBolt, tapered, 44mm offset, 3 position remote lockout
SHOCK	Fox Float SL Performance Elite, 165x45, custom tuned for Liv
COMPONENTS	
HANDLEBAR	Giant Contact SLR XC, composite, 35mm XS: 760mm, S: 760mm, M: 760mm, L: 760mm
GRIPS	Liv XC Pro, 32mm silicone
STEM	Giant Contact SL XC, alloy, 35mm XS: 60mm, S: 60mm, M: 70mm, L: 70mm
SEATPOST	Giant Contact Switch, adjustable dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 140-170mm travel / 30.9 x 470mm
SADDLE	Fi'zi:k Vento Argo R5
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle, T-Type AXS
BRAKES	Shimano XT, hydraulic, Shimano RT-64 centerlock rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano XT BL-M8100
CASSETTE	SRAM GX CS 1275 T-Type, 10x52
CHAIN	SRAM GX T-Type
CRANKSET	SRAM XO T-Type, power meter, alloy chainring 32t, 55mm chainline XS:165mm, S:170mm, M:170mm, L:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant XCR 1 30 carbon WheelSystem, 30mm inner width
HUBS	[F] Giant XC alloy, CenterLock, [R] Giant XC alloy, DT350 internal, 54t ratchet system, CenterLock
SPOKES	Sapim Laser
TIRES	Maxxis Aspen, 29x2.4, foldable, TLR, EXO, tubeless
EXTRAS	tubeless prepared, custom Giant MRP chain guide, 3M clear foil down tube protector, max tire size 2.4-inch, max chainring size 34t. *Not compatible with 2023 or earlier RockShox Sid rear shocks.

Suggested Retail Price (CDN): \$8,999.00

FRAME GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	380	410	440	470
Seat Post Insertion Depth (mm)	203	233	263	293
Seat Tube Angle	76.0°	76.0°	76.0°	76.0°
Top Tube Length (mm)	555	570	585	600
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	67.0°	67.0°	67.0°	67.0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	112.2	112.2	112.2	112.2
Wheelbase (mm)	1121	1137	1154	1170
Chain Stay Length (mm)	435	435	435	435
Bottom Bracket Drop (mm)	45	45	45	45
Stack (mm)	599	603	612	622
Reach (mm)	406	420	432	445
Stand Over Height (mm)	748	767	770	791
Handlebar Width (mm)	760	760	760	760
Stem Length (mm)	60	60	70	70
Crank Length (mm)	165	170	170	175
Wheel Size	29"	29"	29"	29"

All prices and specifications are subject to change without notice.