



PIQUE ADVANCED 29 1



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, L
COLORES	Gloss Raw Carbon/Matte Raw Carbon/Chrome
CUADRO	Advanced-grade composite front and rear triangles, 115mm FlexPoint Pro Suspension
TIJERA	Fox 34 Float SC Performance Elite, 120mm, FIT4 damper, Boost 15x110 KaBolt, tapered, 44mm offset, 3 position remote lockout
AMORTIGUADOR	Fox Float SL Performance Elite, 165x45, custom tuned for Liv
COMPONENTES	
MANUBRIO	Giant Contact SLR XC, composite, 35mm XS: 760mm, S: 760mm, M: 760mm, L: 760mm
GRIPS	Liv XC Pro, 32mm
POTENCIA	Giant Contact SL XC, alloy, 35mm XS: 60mm, S: 60mm, M: 70mm, L: 70mm
POSTE DE ASIENTO	Giant Contact Switch, adjustable dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 140-170mm travel / 30.9 x 470mm
ASIENTO	Fi'zi:k Vento Argo R5
PEDALES	platform
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM AXS, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	SRAM GX Eagle, T-Type AXS
FRENOS	Shimano XT, hydraulic, Shimano RT-64 centerlock rotors [F]180mm, [R]160mm
PALANCAS DE FRENOS	Shimano XT BL-M8100
CASSETTE	SRAM GX CS 1275 T-Type, 10x52
CADENA	SRAM GX T-Type
MULTIPLICACIÓN	SRAM XO T-Type, power meter, alloy chainring 32t, 55mm chainline XS:165mm, S:170mm, M:170mm, L:175mm
EJE DE CENTRO	SRAM DUB, press fit

RUEDAS	
RUEDAS	Giant XCR 1 30 carbon WheelSystem, 30mm inner width
MAZAS	[F] Giant XC alloy, CenterLock, [R] Giant XC alloy, DT350 internal, 54t ratchet system, CenterLock
RAYOS	Sapim Laser
NEUMÁTICOS	Maxxis Aspen, 29x2.4, foldable, TLR, EXO, tubeless
EXTRAS	tubeless prepared, custom Giant MRP chain guide, 3M clear foil down tube protector, max tire size 2.4-inch, max chainring size 34t. *Not compatible with 2023 or earlier RockShox Sid rear shocks.

Precio: \$143,990.00

GEOMETRÍA

CUADRO	XS	S	M
Longitud de la Base del Poste de Asiento (mm)	380	410	440
Seat Post Insertion Depth (mm)	203	233	263
Ángulo de la Base del Poste de Asiento	76.0°	76.0°	76.0°
Longitud del Tubo Superior (mm)	555	570	585
Longitud del Telescopio (mm)	90	95	105
Ángulo del Telescopio	67.0°	67.0°	67.0°
Rake (mm)	44	44	44
Trail (mm)	112.2	112.2	112.2
Distancia entre Ejes (mm)	1121	1137	1154
Longitud de Vaina Inferior (mm)	435	435	435
Caída del Eje de Centro (mm)	45	45	45
Stack (mm)	599	603	612
Reach (mm)	406	420	432
Altura del Tubo Superior al Suelo (mm)	748	767	770
Ancho del Manubrio (mm)	760	760	760
Longitud de la Potencia (mm)	60	60	70
Longitud de la Biela (mm)	165	170	170
Tamaño de las Ruedas	29"	29"	29"

Todas las especificaciones están sujetas a cambios sin previo aviso.