

PIQUE ADVANCED 29 1



SPECS

QUADRO	
TAMANHOS	XS, S, M, L
CORES	Gloss Raw Carbon/Matte Raw Carbon/Chrome
QUADRO	Advanced-grade composite front and rear triangles, 115mm FlexPoint Pro Suspension
FORQUILHA	Fox 34 Float SC Performance Elite, 120mm, FIT4 damper, Boost 15x110 KaBolt, tapered, 44mm offset, 3 position remote lockout
AMORTECEDORES	Fox Float SL Performance Elite, 165x45, custom tuned for Liv
COMPONENTES	
GUIADOR	Giant Contact SLR XC, composite, 35mm XS: 760mm, S: 760mm, M: 760mm, L: 760mm
PUNHOS	Liv XC Pro, 32mm
AVANÇO	Giant Contact SL XC, alloy, 35mm XS: 60mm, S: 60mm, M: 70mm, L: 70mm
ESPIGÃO DE SELIM	Giant Contact Switch, adjustable dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 140-170mm travel / 30.9 x 470mm
SELIM	Fi'zi:k Vento Argo R5
PEDAIS	platform
TRANSMISSÃO	
MANETES	SRAM AXS, 1x12
DESVIADOR DIANTEIRO	N/A
DESVIADOR TRASEIRO	SRAM GX Eagle, T-Type AXS
TRAVÕES	Shimano XT, hydraulic, Shimano RT-64 centerlock rotors [F]180mm, [R]160mm
MANÍPULOS DOS TRAVÕES	Shimano XT BL-M8100
CASSETTE	SRAM GX CS 1275 T-Type, 10x52
CORRENTE	SRAM GX T-Type
CONJUNTO PEDALEIRO	SRAM XO T-Type, power meter, alloy chainring 32t, 55mm chainline XS:165mm, S:170mm, M:170mm, L:175mm
MOVIMENTO CENTRAL	SRAM DUB, press fit

RODAS	
AROS	Giant XCR 1 30 carbon WheelSystem, 30mm inner width
CUBOS	[F] Giant XC alloy, CenterLock, [R] Giant XC alloy, DT350 internal, 54t ratchet system, CenterLock
RAIOS	Sapim Laser
PNEUS	Maxxis Aspen, 29x2.4, foldable, TLR, EXO, tubeless
EXTRAS	tubeless prepared, custom Giant MRP chain guide, 3M clear foil down tube protector, max tire size 2.4-inch, max chainring size 34t. *Not compatible with 2023 or earlier RockShox Sid rear shocks.

Preço: 7 299,00 €

GEOMETRIA

QUADRO	XS	S	M	L
Comprimento do tubo do assento (mm)	380	410	440	470
Seat Post Insertion Depth (mm)	203	233	263	293
Ângulo do tubo do assento	76,0°	76,0°	76,0°	76,0°
Comprimento do tubo superior (mm)	555	570	585	600
Comprimento do tubo principal (mm)	90	95	105	115
Ângulo do tubo principal	67,0°	67,0°	67,0°	67,0°
Garfo ancinho (mm)	44	44	44	44
Trilha (mm)	112,2	112,2	112,2	112,2
distância entre eixos (mm)	1121	1137	1154	1170
Comprimento Chain Stay (mm)	435	435	435	435
Suporte inferior (mm)	45	45	45	45
Pilha (mm)	599	603	612	622
Alcançar (mm)	406	420	432	445
Altura do standover (mm)	748	767	770	791
Largura do guidão (mm)	760	760	760	760
Comprimento da haste (mm)	60	60	70	70
Comprimento da Manivela (mm)	165	170	170	175
Tamanho da roda	29"	29"	29"	29"

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.