PIQUE ADVANCED 29 1



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Gloss Raw Carbon/Matte Raw Carbon/Chrome
OKVIR	Advanced-grade composite front and rear triangles, 115mm FlexPoint Pro Suspension
VILICE	Fox 34 Float SC Performance Elite, 120mm, FIT4 damper, Boost 15x110 KaBolt, tapered, 44mm offset, 3 position remote lockout
AMORTIZER	Fox Float SL Performance Elite, 165x45, custom tuned for Liv
KOMPONENTE	
KRMILO	Giant Contact SLR XC, composite, 35mm XS: 760mm, S: 760mm, M: 760mm, L: 760mm
GRIPS	Liv XC Pro, 32mm
OPORA KRMILA	Giant Contact SL XC, alloy, 35mm XS: 60mm, S: 60mm, M: 70mm, L: 70mm
OPORA SEDEŽA	Giant Contact Switch, adjustable dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 140-170mm travel / 30.9 x 470mm
SEDEŽ	Fi'zi:k Vento Argo R5
PEDALA	platform
POGON	
PRESTAVNE ROČICE	SRAM AXS, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM GX Eagle, T-Type AXS
ZAVORE	Shimano XT, hydraulic, Shimano RT-64 centerlock rotors [F]180mm, [R]160mm
ZAVORNE ROČICE	Shimano XT BL-M8100
VERIŽNIK	SRAM GX CS 1275 T-Type, 10x52
VERIGA	SRAM GX T-Type
GONILKE Z VERIŽNIKI	SRAM XO T-Type, power meter, alloy chainring 32t, 55mm chainline XS:165mm, S:170mm, M:170mm, L:175mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant XCR 1 30 carbon WheelSystem, 30mm inner width
PESTA	[F] Giant XC alloy, CenterLock, [R] Giant XC alloy, DT350 internal, 54t ratchet system, CenterLock
NAPERE	Sapim Laser
PLAŠČI	Maxxis Aspen, 29x2.4, foldable, TLR, EXO, tubeless
DODATKI	tubeless prepared, custom Giant MRP chain guide, 3M clear foil down tube protector, max tire size 2.4-inch, max chainring size 34t. *Not compatible with 2023 or earlier RockShox Sid rear shocks.

GEOMETRIJA

OKVIR	XS	S	M	L
Dolžina sedežne cevi (mm)	380	410	440	470
Seat Post Insertion Depth (mm)	203	233	263	293
Kot sedežne cevi	76,0°	76,0°	76,0°	76,0°
Top Tube Length (mm)	555	570	585	600
Višina glave okvirja (mm)	90	95	105	115
Krmilni kot	67,0°	67,0°	67,0°	67,0°
Zamik vpetja osi (mm)	44	44	44	44
Trail (mm)	112,2	112,2	112,2	112,2
Medosna razdalja (mm)	1121	1137	1154	1170
Dolžina cevi ob verigi (mm)	435	435	435	435
Bottom Bracket Drop (mm)	45	45	45	45
Oddaljenost zgornje cevi od gonilne osi (mm)	599	603	612	622
Doseg (mm)	406	420	432	445
Višina zgornje cevi (mm)	748	767	770	791
Širina krmila (mm)	760	760	760	760
Dolžina opore krmila (mm)	60	60	70	70
Dolžina gonilke (mm)	165	170	170	175
Velikost obročnikov	29"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.