

PIQUE ADVANCED 29 2



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Golden Haze/Carbon/Chrome
FRAME	Advanced-grade composite front and rear triangles, 115mm FlexPoint Pro Suspension
VOORVORK	Fox 34 Float SC Performance, 120mm, Grip damper, Boost 15x110 KaBolt, 44mm offset, 3 position remote lockout
DEMPER	Fox Float SL Performance Elite, 165x45, custom tuned for Liv
ONDERDELEN	
STUUR	Giant Contact XC, alloy, 35mm XS: 760mm, S: 760mm, M: 760mm, L: 760mm
HANDVATTEN	Liv XC Pro, 32mm
STUURPEN	Giant Contact SL XC, alloy, 35mm XS: 60mm, S: 60mm, M: 70mm, L: 70mm
ZADELPEN	Giant Contact Switch, adjustable dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 140-170mm travel / 30.9 x 470mm
ZADEL	Fi'zi:k Vento Argo R5
PEDALEN	platform
AFMONTAGE	
SHIFTERS	Shimano XT M8100, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	Shimano XT M8100, Shadow +
REMMEN	Shimano SLX M7100, hydraulic, Shimano RT-56 rotors [F]180mm, [R]160mm
REMHENDELS	Shimano Deore BL-M7100
CASSETTE	Shimano SLX M7100, 10x51
AANDRIJVING	KMC X12
CRANKSET	Shimano SLX M7120-1, alloy chainring 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 175mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant XCR 2 29 carbon WheelSystem, 25mm inner width
NAVEN	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPAKEN	Sapim
BANDEN	Maxxis Aspen, 29x2.4, foldable, TLR, EXO, tubeless
EXTRA'S	tubeless prepared, custom Giant MRP chain guide, 3M clear foil down tube protector, max tire size 2.4-inch, max chainring size 34t. *Not compatible with 2023 or earlier RockShox Sid rear shocks.

Adviesprijs: € 5.399,00

GEOMETRIE

FRAME	XS	S	M	L
Zitbuis Lengte (mm)	380	410	440	470
Seat Post Insertion Depth (mm)	203	233	263	293
Zitbuis Hoek	76,0°	76,0°	76,0°	76,0°
Frame Lengte (horizontaal) (mm)	555	570	585	600
Balhoofdbuis Lengte (mm)	90	95	105	115
Balhoofdbuis Hoek	67,0°	67,0°	67,0°	67,0°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	112,2	112,2	112,2	112,2
Wielbasis (mm)	1121	1137	1154	1170
Liggende achtervork lengte (mm)	435	435	435	435
Bottom Bracket Drop (mm)	45	45	45	45
Stack (mm)	599	603	612	622
Reach (mm)	406	420	432	445
Stand Over Height (mm)	748	767	770	791
Stuur breedte (mm)	760	760	760	760
Stuurpen Lengte (mm)	60	60	70	70
Cranklengte (mm)	165	170	170	175
Wielmaat	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.