

# PIQUE ADVANCED 29 2



## SPECS

RAMME	
STØRRELSE	XS, S, M, L
FARGE	Golden Haze/Carbon/Chrome
RAMME	Advanced-grade composite front and rear triangles, 115mm FlexPoint Pro Suspension, 12x148mm thru-axle
GAFFEL	Fox 34 Float SC Performance Remote, 120mm, GRIP damper, Boost 15x110 KaBolt, 44mm offset, 3 position remote lockout
DEMPER	Fox Float SL Performance Elite, 165x45, custom tuned for Liv, recommended sag 25%
KOMPONENTER	
STYRE	Giant Contact XC Flat, 760x35mm
GRIPS	Liv XC Pro, 32mm
STYRSTEM	Giant Contact SL XC, alloy, 35mm XS: 60mm, S: 60mm, M: 70mm, L: 70mm
SETEPINNE	Giant Contact Switch AT dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 140-170mm travel / 30.9 x 470mm
SADEL	Liv Grit SL
DRIVVERK	
GIRHENDLER	Shimano Deore XT SL-M8100, 1x12
FRONTGIR	N/A
BAKGIR	Shimano Deore XT RD-M8100, Shadow+
BREMSER	Shimano SLX BR-M7100, hydraulic, Shimano RT-56 rotors [F]180mm, [R]160mm
BREMSEHENDLER	Shimano Deore BL-M7100
KASSETT	Shimano XT, M8100, 10x51
KJEDE	KMC X-12
KRANK	Shimano XT M8120, 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 175mm
BOTTOM BRACKET	Shimano, press fit

HJUL	
FELG	Giant XCR 2.29 Carbon WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
EIKE	Sapim
DEKK	Maxxis Aspen 29x2.4, foldable, 120tpi, TLR, EXO, tubeless
EXTRAS	tubeless prepared, custom Giant MRP chain guide, 3M clear foil down tube protector, max tire size 2.4-inch, max chainring size 34t

## GEOMETRI

RAMME	XS	S	M	L
Seat Tube Length (mm)	380	410	440	470
Seat Post Insertion Depth (mm)	203	233	263	293
Seat Tube Angle	76,0°	76,0°	76,0°	76,0°
Top Tube Length (mm)	555	570	585	600
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	67,0°	67,0°	67,0°	67,0°
Fork Rake (mm)	44	44	44	44
Trail (mm)	112,2	112,2	112,2	112,2
Wheelbase (mm)	1121	1137	1154	1170
Chain Stay Length (mm)	435	435	435	435
Bottom Bracket Drop (mm)	45	45	45	45
Stack (mm)	599	603	612	622
Reach (mm)	406	420	432	445
Stand Over Height (mm)	748	767	770	791
Handlebar Width (mm)	760	760	760	760
Stem Length (mm)	60	60	70	70
Crank Length (mm)	165	170	170	175
Wheel Size	29"	29"	29"	29"

Alle spesifikasjonene kan endres uten varsel.