

PIQUE ADVANCED 29 2



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XS, S, M, L
FARBY	Golden Haze/Carbon/Chrome
RÁM	Advanced-grade composite front and rear triangles, 115mm FlexPoint Pro Suspension
VIDLICA	Fox 34 Float SC Performance, 120mm, Grip damper, Boost 15x110 KaBolt, 44mm offset, 3 position remote lockout
TLMIČ	Fox Float SL Performance Elite, 165x45, custom tuned for Liv
KOMPONENTY	
RIADIDLÁ	Giant Contact XC, alloy, 35mm XS: 760mm, S: 760mm, M: 760mm, L: 760mm
GRIPY	Liv XC Pro, 32mm
PREDSTAVEC	Giant Contact SL XC, alloy, 35mm XS: 60mm, S: 60mm, M: 70mm, L: 70mm
SEDOVKA	Giant Contact Switch, adjustable dropper, remote XS: 110-140mm travel / 30.9 x 395mm S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 140-170mm travel / 30.9 x 470mm
SEDADLO	Fi'zi:k Vento Argo R5
PEDÁLE	platform
POHON	
RADENIE	Shimano XT M8100, 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	Shimano XT M8100, Shadow +
BRZDY	Shimano SLX M7100, hydraulic, Shimano RT-56 rotors [F]180mm, [R]160mm
BRZDOVÉ PÁKY	Shimano Deore BL-M7100
KAZETA	Shimano SLX M7100, 10x51
REŤAZ	KMC X12
KLUKY	Shimano SLX M7120-1, alloy chainring 30t, 55mm chainline XS: 165mm, S: 170mm, M: 170mm, L: 175mm
STREDOVÉ ZLOŽENIE	Shimano, press fit

KOLESÁ	
RÁFIKY	Giant XCR 2 29 carbon WheelSystem, 25mm inner width
NÁBOJE	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
ŠPICE	Sapim
PNEUMATIKY	Maxxis Aspen, 29x2.4, foldable, TLR, EXO, tubeless
DOPLNKY	tubeless prepared, custom Giant MRP chain guide, 3M clear foil down tube protector, max tire size 2.4-inch, max chainring size 34t. *Not compatible with 2023 or earlier RockShox Sid rear shocks.

Cena: 5 399 €

GEOMETRIA

RÁM	XS	S	M	L
Dĺžka sedlovej trubky (mm)	380	410	440	470
Hĺbka vloženia sedlovky (mm)	203	233	263	293
Uhol sedlovej trubky	76,0°	76,0°	76,0°	76,0°
Dĺžka hornej rámovej trubky (mm)	555	570	585	600
Dĺžka hlavovej trubky (mm)	90	95	105	115
Uhol hlavovej trubky	67,0°	67,0°	67,0°	67,0°
Offset vidlice (mm)	44	44	44	44
Trail (mm)	112,2	112,2	112,2	112,2
Rázvor (mm)	1121	1137	1154	1170
Dĺžka zadnej stavby (mm)	435	435	435	435
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	45	45	45	45
Stack - výška riadenia (mm)	599	603	612	622
Reach (mm)	406	420	432	445
Výška rámu od zeme (mm)	748	767	770	791
Šírka riaditok (mm)	760	760	760	760
Dĺžka predstavca (mm)	60	60	70	70
Dĺžka klúku (mm)	165	170	170	175
Rozmer kolies	29"	29"	29"	29"

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.